

INDEPENDENT LOCK COMPANY

COMBINED
STOCK
CATALOG
No.
255

LOCKWOOD HARDWARE MFG. CO.



GENERAL OFFICES: FITCHBURG, MASS.

CATALOG NO. 25S

FOREWORD

This catalog marks a new milestone in the histories of Independent Lock Company and Lockwood Hardware Manufacturing Company.

Independent Lock Company was founded in 1917 — Lockwood Hardware Manufacturing Company in 1878. In 1931, Independent Lock Company purchased Lockwood Hardware Manufacturing Company and in 1932 merged the manufacturing facilities of both Companies into an expanded plant in Fitchburg, Mass. While the products of each company have retained their respective brand names and have been marketed by separate sales divisions over the years, new product development and product improvement have inevitably resulted in duplicate lines of certain stock items.

After careful review of all factors involved, it is clear that a greatly improved service, to customers of both Companies, will be effected by cataloging and packaging duplicate stock items under a single brand.

This COMBINED STOCK CATALOG NO. 25S, lists the stock items selected from each brand. In addition to items included in this catalog, key blanks and lock-smith's supplies will continue under the ILCO brand.

The ultimate benefits of this consolidation of two outstanding brand names in the hardware industry will be shared by all.


Copyright 1961 Independent Lock Co. Fitchburg, Mass.


CONTENTS


INDEX

ITEMS	BRAND	PAGES	ITEMS	BRAND	PAGES
Bolts,			Latches,		
Extension	Lockwood	17	Long Backset	Lockwood	8
Mortise	Ilco	25	Screen & Storm Door	Lockwood	16
Cabinet Locks	Ilco	21	Letter Drop	Lockwood	17
Coin Machine Locks	Ilco	21	Locker Locks	llco	21
Cylinders	Ilco-Lockwood	32	Madison Design	Lockwood	14
Cylindrical Locks,			Marine Padlocks	llco	23
"D" Series	Lockwood	8	Merchandisers	Ilco-Lockwood	36, 37
"R" Series	Lockwood	4, 5	Mortise Bolts	Ilco	25
"S" Series	Lockwood	6,7	Mortise Deadlocks	Lockwood	25
Deadlocks,			Mortise Locksets	Lockwood	14
Jimmyproof	llco	19	Mounts	Ilco-Lockwood	36-39
Mortise	Lockwood	25	Mullion	Lockwood	30
Rim	Ilco	19	Night Latches, Rim	Ilco	18, 19
Tubular	Lockwood	25	Padlocks	llco	22-24
Desk Locks	llco	21	Padlock Assortments	llco	39
Door Closers,			Panel Locks	llco	21
Hydraulic	Ilco	26-29	Panic Exit Devices	Lockwood	30, 31
Pneumatic	Lockwood	16	Phone Dial Lock	Ilco	33
Door Knockers	Lockwood	17	Pull, Sliding Door	Lockwood	12
Dorguard	Lockwood	9	Remodelor	Lockwood	9
Drawer Locks	Ilco	21	Rim Deadlocks	Ilco	19
Entrance Handle Sets	Lockwood	15	Rim Locksets	Lockwood	17
Escutcheons	Ilco	33	Ring, Extension	Lockwood	12
Extension Bolts	Lockwood	17	Screen & Storm Door		
Extension Ring	Lockwood	12	Closers	Lockwood	16
Exit Devices	Lockwood	30, 31	Screen & Storm Door		
Garage Door Locks	Ilco	20	Latchsets	Lockwood	16
Gate Catch	Ilco	25	Screen & Storm Door		
Handle Locksets	Lockwood	15	Locksets	Lockwood	16
Jimmyproof Deadlocks	Ilco	19	Sliding Door Hardware		12
Key Blank Assortment	Ilco	35	Speedrils	Lockwood	12, 13
Key Blanks	Ilco	40	Telephone Dial Lock	llco	33
Key Blank Displays	Ilco	35	Tool Chest Locks	llco	21
Key Cutting Machines	Ilco	34, 35	Trim Plates	Lockwood	10, 11
Key Hole Lock	Ilco	33	Tubular Deadlocks	Lockwood	25
Keying Kits	Ilco	32	TyKees	Lockwood	33
Knobs, Replacement	Ilco	33	Vending Machine Locks		21
Knockers	Lockwood	17	Wardrobe Locks	Ilco	21

LOCKWOOD RESIDENTIAL CYLINDRICAL LOCKSETS








FEATURES

REVOLUTIONARY DESIGN —
FOR QUICK, TROUBLE-FREE INSTALLATION



Note round and square sleeves that mate with round and square grooves. These prevent accidental misassembly.



Outside unit slides onto latch case and its jaws engage the notches in upper and lower sides of case.

Inside unit slips easily into place with its round and square grooves engaging the round and square sleeves.

SELF-ALIGNING LATCH — Notches in latch case permit latch to swivel, yet function smoothly, even when door is improperly bored, or has a beveled edge.

*REVOLUTIONARY MATERIALS —
INTERNAL PARTS OF INDUSTRIAL NYLON OFFER
MANY EXCLUSIVE FEATURES

OUTWEARS SIMILAR METAL PARTS — Laboratory and field tests prove this modern material outlasts and outperforms similar metal parts, by a wide margin.

RUSTLESS—NEEDS NO LUBRICATION — Withstands extremes of humidity, temperature and corrosive atmosphere. Low frictional drag assures continuous performance without lubrication.

WON'T RATTLE LOOSE — Elasticity of this modern miracle material keeps central assembly under tension and automatically adjusts to door shrinkage. Prevents throughbolts from vibrating loose.

IDEAL REPLACEMENT SETS — Fit 2" diameter hole — will replace most residential cylindrical locks.

SPECIFICATIONS

Cylindrical Mechanism — Nylon, $1^{15}/_6$ " diameter. Installs in 2" or $2 \frac{1}{8}$ " diameter hole.

Backset — Regularly furnished 2 %". *Can be furnished 5" backset when so ordered. (See page 8).

 † Latch — Nylon. Installs in ~% " diameter holes. Front, 2~% " x 1".

 † Strike — Size 2 $^{1}/_{4}$ " x 1 $^{13}/_{16}$ " with curved full lip 1 $^{1}/_{4}$ " to center of hole.

Cylinder — Solid brass, 5 pin tumbler. Two keys No. 325.

Keying — Furnished keyed alike when so ordered. Can be masterkeyed with other 5 pin tumbler Lockwood locks having No. B 325 or No. B308 key.

Door Thickness — For doors 1 3/8" to 1 3/4" thick.


Hand — Non-cylinder sets are universal. Cylinder sets are reversible.


Also available in all brass and steel construction — same designs, finishes and functions but with snap-on roses. See price list. In placing orders, prefix description with symbol "X". For example, XRT110X3.


LOCKSETS	DESCRIPTION	DESIGNS AND SET NUMBERS THUNDERBIRD STARFIRE DELMAR			30 PE	CKED R CASE HT, LBS.
	OF FUNCTIONS	☐ RT	☐ RS	☐ RD	Brass or Bronze	Alumi- num
	FOR PASSAGE DOORS By Knob either side at all times.	No. RT110 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS110 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD110 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	32	24
	FOR CLOSET DOORS By Knob outside, thumbturn inside at all times.	No. RT115 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS115 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD115 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	28	24
	FOR BATH AND BEDROOM DOORS By Knob either side, except when outside knob is locked by push button. Turning inside knob or closing door automatically releases outside knob. Emergency key unlocks outside knob.	10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS120 *Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome om specify — x 2		33	25
WITH TURN BUTTON	FOR PATIO OR PORCH DOORS No. 123DL has deadlocking latch. No. 123 has plain latch. By knob either side, except when outside knob is locked by turnbutton in inside knob.	No. RT123DL or RT123 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS123DL or RS123 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD123DL or RD123 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	33	25
WITH PUSH BUTTON	FOR PATIO OR PORCH DOORS No. 124DL has deadlocking latch. No. 124 has plain latch. By Knob either side, except when outside knob is locked by pushbutton in inside knob. Turning inside knob or closing door unlocks outside knob.	No. RT124DL or RT124 Finishes — 3 Bright Brass 10 Dull Branze 26 Bright Chrome 26D Dull Chrome	No. RS124DL or RS124 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD124DL or RD124 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	33	25
WITH TURN BUTTON	FOR EXTERIOR DOORS No. 130DL has deadlocking latch. No. 130 has plain latch. By knob either side except when outside knob is locked by turnbutton, then by key outside.	No. RT130DL or RT130 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS130DL or RS130 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD130DL or RD130 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	40	32
	FOR VESTIBULE OR STORAGE DOORS No. 134DL has deadlocking latch. No. 134 has plain latch. By knob inside at all times. Outside knob always rigid. Key retracts bolt.	No. RT134DL or RT134 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. R\$134DL or R\$134 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD134DL or RD134 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	40	32
	DUMMY TRIM For use as door pull. Furnished with wood screws. Also with throughbolts, when so ordered.	No. RT10 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RS10 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. RD10 Finishes — 3 Bright Brass 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	60 p	er case

"S" SERIES

LOCKWOOD STANDARD DUTY CYLINDRICAL LOCKSETS







FEATURES

Lockwood standard duty cylindrical locksets are the result of a bold new engineering approach which has brought a degree of solidity, durability and smoothness of performance not previously available in locksets of this class. Manufactured to close tolerances on the most modern equipment and employing only highest grade, time-tested materials — brass, bronze, aluminum and steel, this series of locksets assures long, trouble-free performance. Some of its outstanding features are as follows.

SCREW-ON ROSES — See below.

LONG BEARING KNOB SHANKS — These are supported in extra-long sleeves eliminating knob-wobble.

LONG THROW BOLT — Solid brass with full 1/2" throw.

ENDURING SECURITY — Entry locks have solid brass 5 pin tumbler cylinder.

SECURE MASTERKEYING — Deep pin chamber permits secure masterkeying.

PANIC-PROOF — Inside knob is never locked.

AUTOMATIC KICKOFF — Prevents accidental lockout on bathroom and bedroom sets.

SPECIFICATIONS

Cylindrical Case — Steel, dichromated, $2\frac{1}{16}$ diameter. Requires $2\frac{1}{8}$ diameter hole in door stile.

Backset — Regularly furnished 2%". Can be furnished 5", 7" and 10" backset when so ordered.

To order, merely add backset wanted to set number. Example: No. SA130DL x 5"B.S. (See also page 8.)

Latch — Steel, dichromated case ${}^{27/32}$ " diameter. Front, wrought brass, bronze or aluminum, $2 \frac{1}{4}$ " x 1". Regularly furnished flat front. Can be furnished beveled $\frac{1}{8}$ " in 2" when so ordered. Solid brass bolt with $\frac{1}{2}$ " throw. Requires $\frac{1}{8}$ " diameter hole in door


Strike — Wrought brass or bronze, $2\frac{3}{4}$ " x $1\frac{1}{8}$ ". Regularly furnished with curved lip $1\frac{1}{4}$ " to center and with wrought box. Other length lips to order.

Cylinder — Solid brass, 5 pin tumbler. Two keys No. B308.

Keying — Furnished Keyed Alike, symbol KA when so ordered. Can be masterkeyed with other Lockwood locks having No. B308 key

Door Thickness — For doors 1 3/8" to 1 3/4" thick.

Hand — Non-cylinder sets are universal. Cylinder sets are reversible.




FEATURES SCREW-ON ROSES

All "S" Series lock and latch sets have two screw-on roses as illustrated. These enable exact centering of the mechanism in the door with resulting equalized knob projection on both sides. The installation is unusually secure and later adjustment to compensate for door shrinkage is easily accomplished by merely tightening the inside rose with the spanner wrench furnished. No parts need be removed.

	DESCRIPTION	DESIGNS AND SET NUMBERS				KED CASE
LOCKSETS	OF FUNCTIONS	AMHERST SA	ELDORADO SE	DALLAS	WEIGH Brass or	T, LBS.
	FOR PASSAGE DOORS By knob from either side at all times.	No. SA110 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SE110 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD110 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	32	27
	FOR CLOSET DOORS By knob outside, thumbturn inside at all times.	No. SA115 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SE115 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD115 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	32	27
	FOR BATH AND BEDROOM DOORS By knob either side, except when outside knob is locked by pushbutton. Turning inside knob or closing door automatically releases outside knob. Emergency key unlocks outside knob *For bathroom specify — x26 inside.	10 Dull Bronze	No. SE120 *Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD120 *Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	33	28
WITH TURN BUTTON	FOR PATIO OR PORCH DOORS By knob either side, except when outside knob is locked by turnbutton in inside knob.		No. SE123DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD123DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	33	28
WITH PUSH BUTTON	FOR PATIO OR PORCH DOORS By knob either side, except when outside knob is locked by pushbutton in inside knob. Turning inside knob or closing door unlocks outside knob.	No. SA124DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SE124DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD124DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	33	28
WITH TURN BUTTON	FOR EXTERIOR DOORS Has deadlocking latch. By knob either side, except when outside knob is locked by turnbutton, then by key outside. Inside knob always free.	No. SA130DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SE130DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD130DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	38	33
WITH PUSH BUTTON	FOR EXTERIOR DOORS Has deadlocking latch. By knob either side, except when outside knob is locked by pushbutton. Then by key outside. Turning inside knob or key outside releases locking mechanism. Closing door does not.	No. SA137DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SE137DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD137DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	38	33
WITH UNIVERSAL BUTTON	FOR MOTEL GUEST ROOM DOORS Has deadlocking latch. By knob inside at all times. Outside knob always rigid. Pushing button projects indicator in cylinder. Then from outside by emergency key only. Turning inside knob, or closing door, releases button if merely pushed in, but not if pushed in and turned.	10 Dull Bronze 26 Bright Chrome	10 Dull Bronze 26 Bright Chrome	No. SD140DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	38	33
	FOR CLOSET OR COMMUNICATING DOORS Has deadlocking latch. By thumbturn inside at all times. Key locks knob only.	Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	No. SD146DL Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	38	33
	For use as door pulls. Furnished with mounting plate and screws.	10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	No. SD10 Finishes — 3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome 28 Satin Alum.	60 per	case 22

LOCKWOOD CYLINDRICAL LOCKSETS



SPECIFICATIONS

Cylindrical Case — Steel, dichromated, $2\frac{1}{6}$ diameter. Requires $2\frac{1}{6}$ diameter hole in door stile.

Backset — Regularly furnished 2 %". Can be furnished 5", 7" and 10" backset when so ordered. To order, merely add backset to set number. Example: No. DA130DLx5"B.S.

Latch — Steel, dichromated case $^{27}\!\!/_{32}$ " diameter. Front, wrought brass, bronze or aluminum, $2\frac{1}{4}$ " x 1". Regularly furnished flat front. Can be furnished beveled $\frac{1}{8}$ " in 2" when so ordered. Solid brass bolt with $\frac{3}{8}$ " throw. Requires $\frac{7}{8}$ " diameter hole in door.

Strike — Wrought brass, bronze or aluminum, $2\frac{1}{4}$ " x $1\frac{13}{16}$ ". Has curved, full lip $1\frac{1}{4}$ " to center.

Cylinder — Die cast, 5 pin tumbler. Two keys No. B308.

Keying — Furnished Keyed Alike, symbol KA, when so ordered.

Door Thickness — For doors 1 3/8" to 1 3/4" thick.

Hand — Non-cylinder sets are universal. Cylinder sets are reversible.

LOCKSETS	DESCRIPTION OF FUNCTIONS	FINISHES	PACKED 20 PER CASE WEIGHT LBS.
WITH TURN BUTTON	FOR EXTERIOR DOORS No. DT130DL has deadlocking latch. No. DT130 has plain latch. By knob either side, except when outside knob is locked by turn button, then by key outside. Inside knob always free.	3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	38
WITH PUSH BUTTON	FOR EXTERIOR DOORS No. DT137DL has deadlocking latch. No. DT137 has plain latch. By knob either side, except when outside knob is locked by push button. Then by key outside.	3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	38

SPECIAL FRONTS AND STRIKES



ROUND CORNERED FRONTS AND STRIKES

Can be furnished with corners rounded to ½" radius, symbol NH, or ¼" radius symbol RH. To order, add symbol to set number; example RT130DLxNH.



ROUND FRONT - SURFACE TYPE

Can be furnished with 1" diameter front which is surface-mounted. Front is $\frac{1}{16}$ " thick and is beveled $\frac{1}{8}$ " in 2". Furnished with round strike. See below. To order, add symbol SR to set number; example PT130DLYSR



ROUND FRONT - MORTISE TYPE

Can be furnished with 1'' diameter front which is mortised into edge of door. Front is $\$/_{32}''$ thick and is not beveled. Furnished with round strike. See below. To order, add symbol MR to set number; example RT130DLxMR.



ROUND STRIKE

Furnished with round front latches. Requires mortise $1\frac{3}{4}$ " diameter and $\frac{1}{16}$ " deep. Has curved lip $1\frac{7}{6}$ " to center of opening. Has adjustable tab to prevent door rattle.

LONG BACKSET LATCHES

FOR "R" SERIES - 5" BACKSET

No. R5DL — Has deadlocking latch bolt.
No. R5 — Has plain latch bolt.
Packed 12 per box, weight per box 4 lbs.

FOR "S" AND "D" SERIES — 5", 7" AND 10" BACKSET

		OSE EATON	"
FOR FUNCTION	FOR 5" B.S.	FOR 7" B.S.	FOR 10" B.S.
110, 115	\$5	S7	\$10
120	S5P	S7P	S10P
123DL, 130DL, 146DL	S5DL	S7DL	S10DL
124DL, 137DL, 140DL	S5DLP	S7DLP	SIODLP

Packed 6 per box. Weight per box, 5'' B.S., 2 lbs., 7'' B.S., 3 lbs., 10'' B.S., $3\frac{1}{2}$ lbs.

To Order in Sets — Merely add backset desired to set number. Example: RT130x5"B.S.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome, 28 Satin Aluminum.

LOCKWOOD REMODELOR - DORGUARD

LOCKWOOD REMODELOR

REPLACEMENT SETS FOR MODERNIZING DOORS
FOR USE WITH "R", "S", and "D" SERIES CYLINDRICAL LOCKSETS

Each set consists of a pair of attractive escutcheon plates, lock front reinforcing and finishing plates, a strike plate, all necessary screws and complete instructions for installation.

No. 466 REMODELER consists of two escutcheons $7 \frac{1}{2}$ " x $3 \frac{1}{8}$ "; one lock front reinforcing plate 6" x 1"; one lock front finishing plate 6" x 1"; one strike $3 \frac{1}{2}$ " x $1 \frac{1}{8}$ "; all necessary screws.

No. 467 REMODELER consists of two escutcheons $10'' \times 3 \frac{1}{2}''$; one lock front reinforcing plate $8'' \times 1''$; one lock front finishing plate $8'' \times 1''$; one strike $5 \frac{1}{4} \frac{1}{8}$; all necessary wood screws.

No. 468 REMODELER consists of one escutcheon $10'' \times 3 \frac{1}{2}''$; one escutcheon $7 \frac{1}{2}'' \times 3 \frac{1}{8}''$; one lock front reinforcing plate $8'' \times 1''$; one lock front finishing plate $8'' \times 1''$; one strike $5 \frac{1}{4}'' \times 1 \frac{1}{8}''$; all necessary screws.

Packed one set per box, 30 per carton.

Weight per carton, No. 466, 16 lbs.; No. 467, 25 lbs.; No. 468, 23 lbs. Finishes — 3 Bright Brass, 10 Dull Bronze, 26D Dull Chrome.

No. 466 also furnished split finish with 26 Bright Chrome inside, for bathroom doors.

COMPONENT PARTS

- A. Escutcheon, 10" x 3 1/2".
- B. Escutcheon, 7 1/2" x 3 1/8".
- C. Lock front reinforcing plate, 8" x 1".
- D. Lock front reinforcing plate, 6" x 1".
- E. Lock front finishing plate, 8" x 1".
- F. Lock front finishing plate, 6" x 1".
- G. Strike, 5 1/4" x 1 1/8".
- H. Strike, 3 1/2" x 1 1/8".

QUICKLY AND EASILY INSTALLED WITH THE LOCKWOOD SPEEDRIL

LOCKWOOD DORGUARD

FOR DOORS OPENING INWARD ONLY

PERMITS IDENTIFICATION OF VISITOR BEFORE ADMISSION.
ALLOWS ENTRANCE BY KEY FROM OUTSIDE AT ANY TIME.





COMPLETE SECURITY — Chain permits door to open only slightly. Visitor cannot remove chain from outside.


EASY TO OPERATE — To release chain from inside, close door and slide pin from slot. From outside, a turn of the key rotates the slotted plate and ejects pin from slot.

No. 8120 Has Five Pin Tumbler, Solid Brass Cylinder and Two Keys. No. B308. No. 8121 Has Five Pin Tumbler, Pressure Cast Cylinder and Two Keys. No. B313. SIZES — Slotted Plate, 2 ¾ " x 2 ¾ ". Chain Hanger 1 ¾ " x 1 ¾ ". Welded Link Chain 6" long.










LOCKWOOD DECORATIVE TRIM PLATES

FOR USE WITH "R", "S" AND "D" SERIES LOCKSETS

WROUGHT BRASS, BRONZE OR ALUMINUM



NO. *578
Shown With
STARFIRE DESIGN




No. 570 Shown With THUNDERBIRD DESIGN

No.	Size	Minimum Backset	Per Box	Weight Per Box
*578	8 % " x 7 % "	5"	6	1 ½ lbs.
571	5 ½″ dia.	5"	6	5⁄8 lb.
570	7 %" x 3 %"	5"	6	1 1/8 lbs.
566	7½"x3½"	2 3/8 "	6	1 lb.
567	10" x 3 ½"	2 3/8 "	6	1 3/4 lbs.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome, 28 Satin Finish Aluminum.



No. 571 Shown With DALLAS DESIGN



No. 566 Type of 567 Shown With ELDORADO DESIGN

^{*}Not furnished in Aluminum


LOCKWOOD DECORATIVE TRIM PLATES


FOR USE WITH "R", "S" AND "D" SERIES LOCKSETS



No. 572 Shown With THUNDERBIRD DESIGN









No. 576 Shown With STARFIRE DESIGN

No. 574 Shown With AMHERST DESIGN

No.	Size	Minimum Backset	Per Box		eight r Box			
572	5 ½ ″ dia.	5"	6	5/8	lb.			
579	7 1/8 " x 3 1/2 "	5"	6	2 1/2	lbs.			
574	5½" x 5½"	5"	6	5/8	lb.			
	Can be used on square or diamond							
576	3 3/4" x 3 3/4"	2 3/8 "	6	1/2	lb.			
Can be used on square with 2 %" backset or diamond								

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome 26D Dull Chrome, 28 Satin Finish Aluminum.

LOCKWOOD

SLIDING DOOR HARDWARE—EXTENSION RING—SPEEDRIL KIT







No. 721 ¼ screws. No. 723 ¼

No. 721 No. 723

ADJUSTABLE STRIKE

Has adjustable box to compensate for sag of door

SLIDING DOOR LATCHSET

No. 721 For doors 1 \%" thick. Furnished with wood screws. No. 723 For doors 1 \%" thick. Furnished with wood screws.

OPERATION — Tee handle either side disengages catch from strike permitting door to be opened. In closing, catch in bolt automatically engages strike holding door tightly closed.

SLIDING DOOR LOCKSET

No. 721 ¼ For doors 1 % " thick. Furnished with wood screws.

No. 723 4 For doors 1 34" thick. Furnished with wood screws.

OPERATION — Tee handle either side disengages catch from strike permitting door to be opened, except when locking bar in inside handle is depressed. Then both handles are rigid. Pressing opposite end of locking bar releases both handles. Emergency key outside also releases handles. Catch housing serves as pull when door is in pocket.

Simple Installation — A speedril may be used for rapid installation of the pull, on above locksets. They fit cylindrical lock mortise.

Packed one set per box, 30 per case. Weight per case 23 lbs.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome.

Nos. 721 ¼ and 723 ¼ also furnished split finish with 26 inside for bathroom doors.

DESCRIPTION OF PARTS

Material — Pressure cast rustless alloy. Cup escutcheons — $2\%_{16}$ " diameter. Requires $2\%_{16}$ " diameter bored hole. Latch Body — 34" diameter. Requires 36" diameter bored hole. Latch front — $2\%_{16}$ " x 1". Backset — $2\%_{16}$ ".

Bolt projection — $\sqrt[n]{16}$ ". **Hand** — Reversible. **Strike** — $2\sqrt[3]{7}$ x $1\sqrt[3]{8}$ ". Has adjustable box to compensate for sag of door.

SLIDING DOOR PULL



No. 700 One pair pulls, with through

No. 701 Single pull, with wood screws. Packed 30 per carton, Weight per carton, No. 700, 10 lbs.; No. 701, 5 lbs.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome.

EXTENSION RING No. 6 Wrought Brass, Bronze, or Aluminum



For use as shim on unusually thin doors, or to increase rose diameter where oversize hole has been bored. Fits $2\frac{1}{2}$ " diameter roses. Outside diameter $2\frac{3}{4}$ ". Packed 12 per box. Weight per box $\frac{1}{2}$ lb.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome, 28 Satin Aluminum.

SPEEDRIL CARRYING CASE No. 564 (Case Only)



This sturdy, steel case is designed to hold the standard or 5 in. backset units with all accessories. It keeps the tools in good order and protects them against damage. Ideal for rental units — or that "plus sale" when selling a Speedril. Size, $10\frac{1}{2}$ " x $6\frac{1}{2}$ " x $4\frac{3}{8}$ ".


Finish — Dark mottled gray enamel with name "LOCKWOOD SPEEDRIL" in orange letters on cover. Packed one per box.

Also available as complete Kit consisting of Speedril, Bit, Mortising Chisel, Strike Centering Punch. To order state numbers of components wanted. Example: No. $541 \times 542 \times 564$.


LOCKWOOD SPEEDRILS

Patent No. 2,792,797

FOR INSTALLING LOCKWOOD CYLINDRICAL, SLIDING DOOR AND REMODELOR SETS









REDUCE INSTALLATION TIME, GUARANTEE CLEAN-CUT HOLES, IN PERFECT ALIGNMENT. MAKE LIGHT WORK OUT OF HARD LABOR.

HAND OPERATED UNITS

No. 541 For "R", "S", "D" and "H" Series. Adaptable to 2%" or 2%" backset by means of Adapter Bushing.

No. 546 For "R", "S" and "D" Series only 2 % " backset.

No. 555 Bores at 5" backset for "R", "S", "D" and "H"

Series. Has removable edge hole bushing for 1" or % " diameter hole.

All above units include Bit, Handle, Breakthrough Ring and Strike Centering Punch.

Packed one per box. Weight, Nos. 541 and 546, $5\frac{1}{2}$ lbs., No. 555, $5\frac{3}{4}$ lbs.

TO OPERATE

- Clamp onto door with Adjusting Screw which automatically centers Edge Hole Jig in door thickness. Tighten firmly with "C" Clamp Screw.
- 2. Insert threaded shank bit into Feeder Bushing. Close Feeder Bushing and secure it with wing nut.
- 3. Slip handle onto bit and bore hole entirely through stile.

 Breakthrough Ring prevents "splintering out."
- Slip handle off, open Feeder Bushing and push bit out through bored hole.
- Using standard auger and brace, bore edge hole through jig.
- 6. Remove Speedril.
- Use Face Mortising Chisel of proper size to cut outline of mortise for latch face.
- 8. Using standard wood chisel, remove wood from face mortise.

TO LOCATE STRIKE — Insert centering punch into edge hole, close door and press punch. Punch mark shows vertical center line of latch front and horizontal center line of strike.

UNITS FOR USE WITH POWER TOOL

No. 541E For "R", "S", "D" and "H" Series. Adaptable to $2\frac{3}{8}$ " or $2\frac{3}{4}$ " backset by means of Adapter Bushing.

No. 546E For "R", "S" and "D" Series only at 2 %" backset. No. 555E Bores at 5" backset for "R", "S", "D" and "H" Series. Has removable edge hole bushing for %" or 1" diameter hole.

All above units include Chuck Adapter, Bit, Breakthrough Ring and Strike Centering Punch.

Packed one per box. Weight, Nos. 541E and 546E, $4\frac{1}{2}$ lbs., No. 555E, 5 lbs.

TO OPERATE

The bit is inserted before clamping to door. The Chuck Adapter chucked in power tool, slips easily over shank end of No. 547E Bit. A standard auger bit is used for edge hole.


REPLACEMENT INSTALLATION — To alter original boring to receive a new set, Speedril can produce the correct openings as quickly and easily as on new doors.












LOCKWOOD MADISON DESIGN LOCKSETS

TRIM	ТҮРЕ	NUMBER AND DESCRIPTION	FINISHES	PER CASE	WGT. LBS.
		FOR ENTRANCE DOORS — WROUGHT BRASS OR BRONZE No. MD4010 Has $8'' \times 2\frac{1}{2}''$ escutcheon outside, $7'' \times 2\frac{1}{4}''$ inside. No. MD4011 Has $10'' \times 2\frac{3}{4}''$ escutcheon outside, $7'' \times 2\frac{1}{4}''$ inside. OPERATION — Latch bolt by knob inside at all times. Stop button locks outside knob. Then by key only outside. Dead bolt by key outside, turnknob inside. Knobs, $2\frac{1}{4}''$ dia., Lock case $5\frac{5}{8}'' \times 3\frac{3}{4}'' \times 3\frac{3}{4}''$. Front forged brass, $7\frac{11}{16}'' \times 1''$. Backset $2\frac{1}{2}''$. Cylinder, 5 pin tumbler. Two keys No. B308. Reversible.	4 Dull Brass 10 Dull Bronze	6	29
		FOR VESTIBULE DOORS — WROUGHT BRASS OR BRONZE No. MD4010 $\frac{1}{2}$ Has $8'' \times 2\frac{1}{2}''$ escutcheon outside, $7'' \times 2\frac{1}{4}''$ inside. No. MD4011 $\frac{1}{2}$ Has $10'' \times 2\frac{3}{4}''$ escutcheon outside, $7'' \times 2\frac{1}{4}''$ inside. OPERATION — Latch bolt by knob inside at all times. Stop button locks outside knob. Then by key only. Knobs, $2\frac{1}{4}''$ dia., Lock case $5\frac{5}{8}'' \times 3\frac{3}{4}'' \times 3\frac{3}{4}''$. Front forged brass, $7\frac{1}{16}'' \times 1''$. Backset $2\frac{1}{2}''$. Cylinder, 5 pin tumbler. Two keys No. B308. Reversible.	3 Bright Brass 4 Dull Brass 10 Dull Bronze 26D Dull Chrome	6	27
		FOR PASSAGE DOORS No. MD4211 Wrought Brass or Bronze. No. MD6204 Wrought Steel, Plated. No. MD6210 Wrought Steel, Plated. OPERATION — By knob or key either side. Knobs, brass, 2" dia.; steel, 2½" dia. twopiece. Escutcheons, 7" x 2½". Lock case, 3½" x 3½" x 5½". Front, 55½" x ½". No. MD6210, 3 tumbler, others one tumbler. Backset, 2¾". Reversible. Nos. MD4211, MD6204, have one key No. 401N. No. MD6210 has one key No. 150SB.	For MD4211 3 Bright Brass 4 Dull Brass 10 Dull Bronze 26D Dull Chrome For MD6204 or MD6210 4 Dull Brass	30	58
		FOR BATH OR BEDROOM DOORS No. MD4211 ¼ Wrought Brass or Bronze. No. MD6204 ¼ Wrought Steel, Plated. OPERATION — Latch bolt by knob either side. Deadbolt by turn knob inside. Emergency Key furnished at extra cost. Knobs, brass, 2" dia.; Steel, 2 ¼" dia. twopiece. Escutcheons, 7" x 2 ¼". Lock case, 3 %" x 3 ¼" x 5%". Front 5 5%" x 7%". Backset 2 3%". Hand, reversible.	For MD4211 1/4 3, 4, 10, 26D or 3x26, 4x26, 10x26, 26Dx26 For MD6204 1/4 4 or 4x14 (Dull Nickel inside)	30	69
Î .		FOR COMMUNICATING DOORS No. MD4221 % Wrought Brass or Bronze. OPERATION — Latch bolt by knob either side. Split deadbolt by turnknob either side. Knobs, 2" dia. Escutcheons, 7" x 2 ¼". Lock case, 313/16" x 35/16" x 5%". Front, 55%" x 7%". Backset, 23%". Reversible.	3 Bright Brass 4 Dull Brass 10 Dull Bronze 26D Dull Chrome	30	70
Φ Φ		LATCH SET — FOR PASSAGE OR CLOSET DOORS No. MD4211 3/3 Wrought Brass or Bronze. OPERATION — By knob from either side. Knobs, 2" dia. Escutcheons, 7" x 2 1/4". Latch case, 1 11/16" x 35/16" x 5/8". Front, 3 3/8" x 15/16". Backset, 29/16".	3 Bright Brass 4 Dull Brass 10 Dull Bronze 26D Dull Chrome	30	53
0		FOR FRONT DOOR No. MD6104 Wrought Steel, Plated. OPERATION — Latch bolt by knob inside at all times. Stop button locks outside knob. Then by key only outside. Deadbolt by key either side. Knobs, 2 ¼" dia. twopiece. Escutcheons inside 7" x 2 ¼". Outside 10" x 2 ¾". Lock case, 5 ¼" x 3 ½" x 5%". Front, 7 ¼" x 1". Backset, 2 ½". Reversible. Two keys No. 403.		6	20

LOCKWOOD RESIDENCE AND STORE DOOR HANDLE LOCKSETS



No. BA2838 BARKLEY DESIGN

Cast Brass or Bronze

OPERATION — Latch bolt by knob inside, thumbpiece outside except when thumbpiece is locked by stop button. Then by key only outside. Deadbolt by key outside, turnknob inside.
(Lock No. T8702 3/4).

Handle, overall $16\frac{3}{8}$ " x $2\frac{1}{2}$ ". Knob, wrought brass or bronze, 2" dia.

One per box, 6 per carton. Weight per carton 31 lbs.

Finishes — 3 Bright Brass, 10 Dull Bronze, 26 Bright Chrome, 26D Dull Chrome.




OPERATION — Latch bolt by knob inside, thumbpiece outside except when thumbpiece is locked by stop button. Then by key only outside. Deadbolt by key outside,


turnknob inside. (Lock No. T87023/4).

Handle, overall $15\frac{9}{8}$ " x $2\frac{3}{4}$ ". Knob, wrought brass or bronze, 2" dia.

One per box, 6 per carton. Weight per carton 32 lbs.

Finish — 92 Imitation Half-Polished Iron.





No. SM2838 SOMERSET DESIGN Cast Brass

OPERATION — Latch bolt by knob inside, thumbpiece outside except when thumbpiece is locked by stop button. Then by key only outside. Deadbolt by key outside turnknob inside. (Lock No. T87023/4).

Handle, overall 161/8" x 21/4". Knob, wrought brass, 2" dia. One per box, 6 per carton. Weight per carton 33 lbs.

Finishes — 3 Bright Brass, 26 Bright Chrome, 26D Dull Chrome.

No. BF2838 BROOKFIELD DESIGN

Cast Brass

OPERATION — Latch bolt by knob inside, thumbpiece outside except when thumbpiece is locked by stop button. Then by key only outside. Deadbolt by key outside turnknob inside. (Lock No. T87023/4).

Handle, overall 17" x 2½". Knob, wrought brass, 2" dia. One per box, 6 per carton. Weight per carton 31 lbs.

Finishes — 3 Bright Brass, 26 Bright Chrome, 26D Dull Chrome.



DESCRIPTION OF LOCKS

Nos. T8702 ¾ and T8705 — Case, 5 ½" x 3 ¾" x ¾". Front, 8" x 1 ¼". Backset, 2 ½". Bolts, cast brass ½" throw. Hand, reversible. Cylinder, solid brass, 5 pin tumbler. Keys, two No. B308. Can be masterkeyed with other Lockwood locks having No. B308 key.

ALTERNATE KNOB DESIGNS

The Residence Handle locksets listed above are available with knobs and roses to match "R" Series cylindrical lock designs. To order, add the design symbol to the handle set number. Example: No. BA2838 RT Knob.

No. MD4848 MADISON DESIGN

Wrought Brass

OPERATION — Latch bolt by thumbpiece either side. Deadbolt by key either side. (Lock No. T8705). Plates, 14 ½" x 3".


One per box, 6 per carton. Weight per carton 41 lbs.

Finish — 3 Bright Brass 26 Bright Chrome.



LOCKWOOD SCREEN AND STORM DOOR HARDWARE

	NUMBER AND DESCRIPTION	FINISHES	PER CASE	WGT. LBS.
	No. 8597 For doors 1 1/8" to 1 3/8" thick. Wrought Brass, Bronze or Aluminum.	3 Bright Brass 10 Dull Bronze	60	50
No. 8597	OPERATION — By knob outside or lever inside, except when both are locked by slide-stop. Double compression spring gives light bolt action, firm knob and lever action. Knob, 1 3/4" dia. Projection, 1 15/16". Lever, 1 1/8" long. Projection, 1 3/8". Escutcheons, 4" x 1 3/8". Case, 3/4" x 2 5/8". Backset, 1 3/4".	28 Satin Alum.	60	35
	No. 8596 For doors 1 1/8" thick. No. 8595 For doors 1 3/8" thick. Wrought Brass, Bronze or Aluminum.			
Nos.	OPERATION — By knob outside or lever inside, except when both are locked by key or slide-stop. Double compression spring gives light bolt action, firm knob and lever action. Knob,	3 Bright Brass 10 Dull Bronze	60	56
8596 8595	$1\frac{3}{4}^{\prime\prime}$ dia. Projection, $1\frac{15}{16}^{\prime\prime}$. Lever, $1\frac{7}{8}^{\prime\prime}$ long. Projection, $1\frac{3}{8}^{\prime\prime}$. Escutcheons, $4^{\prime\prime}$ x $1\frac{3}{8}^{\prime\prime}$. Case, $\frac{3}{4}^{\prime\prime}$ x $2\frac{5}{8}^{\prime\prime}$. Backset, $1\frac{3}{4}^{\prime\prime}$. Two keys No. B350.	28 Satin Alum.	60	40
No. 5599	No. 5599 For doors 1 ½" thick. Wrought Steel, Plated. OPERATION — By knob outside or lever inside, except when both are locked by slide-stop. Knob, 1 ¾" dia. Projection, 1 ½%". Lever, 1 ½" long. Projection, 1 ½". Escutcheons, 4" x 1 ½". Case, 1 ½" x 1 ¾" x ½". Front, 2 ½" x 1 ½". Backset, 1 ¼".	4 Dull Brass	60	46
No. 4125	No. 4125 For doors $\frac{7}{8}$ " to $1\frac{3}{8}$ " thick, opening out. Wrought Steel, Plated. OPERATION — By knob outside or lever inside, except when both are locked by slide-stop. Knob, $1\frac{3}{4}$ " dia. Projection, $1\frac{15}{16}$ ". Lever, $1\frac{7}{8}$ " long. Projection, $1\frac{3}{8}$ ". Escutcheons, 4" x $1\frac{3}{8}$ ". Case, $2\frac{1}{4}$ " x 2". Backset, $1\frac{1}{4}$ ".	3 Bright Brass	60	43
No. 4120	No. 4120 For doors 1 ½" to 1 ¾" thick. Die Cast Alloy, Plated. OPERATION — Pushing handle inside or pulling outside disengages latch. Slide-stop locks both. Automatic kickoff prevents accidental lockout. Levers, 2 ¾" long. Projection, 1 ½". Plates, 2 ½" x 2 ½".	3 Bright Brass	30	33





No. 3006 CLOSER

DESCRIPTION: Size overall $17 \frac{1}{4}$ ". One-piece forged aluminum tube, $1 \frac{1}{2}$ " diameter provides 20% more air cushion. Heavy, concealed compression type spring. Universal for right or left hand doors. Nylon bearing surfaces never need lubrication. Precision speed control. Hold-open ring holds door open at any desired angle.

Finish — Satin aluminum.

Packed — 1 Doz. per case, Weight 15 lbs.

LOCKWOOD RIM LOCKSETS AND DOOR ACCESSORIES

	NUMBER AND DESCRIPTION	FINISHES	PER CASE	WGT. LBS.
9 Set No. 7536S	No. 75365 Cast Iron Lock, Steel Trim. OPERATION — Latch bolt by knob either side, except when deadlocked by stop on case. Dead bolt by key either side. Knobs, 2 ¼ " dia., twopiece. Rose 2" dia. Escutcheon, 1 ¾ " x ¾ ". Lock case, 3 ½ " x 3 ½ ". Backset, 2 ¾ ". Reversible. One per box.	Japanned	30	54
O Set No. 7110S	No. 7110S Cast Iron Lock, Steel Trim. OPERATION — Latch bolt by knob either side, except when deadlocked by stop on case. Dead bolt by key either side. Knobs, 2 ¼" dia., twopiece. Rose 2" dia. Escutcheon, 1 ¾" x ¾". Lock case, 3 ¼" x 4 ½". Backset, to keyhole, 2 ¾", to knob, 3 ½". Reversible. One per box.	Japanned	30	53
No. 8111	EXTENSION FLUSH BOLT No. 8111 Cast Brass, Bronze or Aluminum. Lengths 8", 12", 18", 24". State length. Length is measured from center of lever to end of bolt when retracted. Plate, 6 5%" x 1 1/4". Bolt head 1/2" square, 7/8" throw.	3 Bright Brass 10 Dull Bronze 26D Dull Chrome 28 Satin Aluminum	30	24
	DOOR KNOCKERS No. 8969 Overall size 7 % " x 4". Cast brass. Individually packed in a plastic top box.	3 Bright Brass	6	15
No. 8969 No. 8967	No. 8967 Overall size $6 \frac{1}{2}$ " x $3 \frac{1}{2}$ ". Cast brass. Individually packed in a plastic top box.	3 Bright Brass	6	14
No. 8970	No. 8970 Overall size $8\%'' \times 2\%''$. Cast brass. Individually packed in a plastic top box.	3 Bright Brass	6	17
Front Plate with Hinged Flap Backplate	LETTER DROP No. 8278 Wrought brass or bronze. Plates 2 1/8 " x 9". Opening 1 1/2" x 7". Packed complete with screws in one box.	3 Bright Brass 10 Dull Bronze	6	7 1/2

ILCO NIGHT LATCHES

ТҮРЕ	NUMBER & FINISH	DESCRIPTION	PER CASE	WGT. LBS.
Nos. 263GY, 264GY	No. 263GY No. 264GY Gray Mottle	Cylinder — 263GY, Die Cast, 5 pin tumbler, 2 keys No. X1054F, 264GY, Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Die Cast, 3¾" x 2½" x 1½", standard 2¾" backset. Brass turnknob. Reversible. Die Cast bolt, brass plated. For doors 1¼" to 2½" thick. Operation — From outside by key, which holds latch bolt retracted until key is withdrawn, from inside by knob. Bolt may be held back by stop in case.	30	42
No. 265	No. 265 Brown Pebble	Cylinder — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Cast Iron, 3¾" x 2½" x 1½", standard 2¾" backset. Brass turnknob. Reversible. Cast Iron bolt, Brass plated. For doors 1¼" to 2½" thick. Operation — From outside by key, which holds latch bolt retracted until key is withdrawn, from inside by knob. Bolt may be held back by stop in case.	30	55
No. D218C	No. D218C Gold Bronze Wrinkle	Cylinder — Die Cast, 5 pin tumbler, 2 keys No. X1054F. Case — Die Cast, 2 ½" x 3 ½" x 1", standard 2 ¾" backset. Brass turnknob. Reversible. Die Cast bolt, brass plated. For doors 1 ¼" to 2 ½" thick. Operation — From outside by key, from inside by knob. Bolt may be deadlocked by stop from inside so that key will not turn. Bolt may also be held back by stop in case.	30	36
Nos. 218, 219, 201, 218C, 219C, 0201B	No. 218 No. 219 No. 201 Black Wrinkle No. 218C No. 219C Gold Bronze Wrinkle No. 0201B Natural Bronze	Cylinder — Nos. 218, 218C Die Cast, 5 pin tumbler, 2 keys No. X1054F. Nos. 219, 219C, 201, 0201B solid brass. 5 pin tumbler, 2 keys No. X1054K. Case — Cast Iron, (except 0201B which is cast bronze) 2 ½" x 3 %" x 1". Backset 2 %". Brass turnknob. Reversible. Cast Iron bolt, brass plated, (except Nos. 201, 0201B which is solid brass). For doors 1 ¼" to 2 ½" thick. Operation — From outside by key, from inside by knob. Bolt may be held back by stop in case. Nos. 201, 0201B bolt may also be deadlocked by stop from inside so that key will not turn.	30	50
Nos. D220, D221	No. D220 No. D221 Rose Gold	Cylinder — Die Cast, 5 pin tumbler, 2 keys No. X1054F. Case — Die Cast, 2 ½ " x 3 5% " x 1", standard 2 3% " backset. Brass turnknob. Reversible. Die Cast bolt, brass plated. For doors 1 ¼ " to 2 ½" thick. Operation — From outside by key, from inside by knob. Bolt may be held back by stop in case. No. D221 bolt may also be deadlocked by stop from inside so that key will not turn.	30	36
Nos. 210, 210S, 210B, 210Y	No. 210 No. 2105 No. 210Y Black Wrinkle No. 210B Gold Bronze Wrinkle	Cylinder — Nos. 210, 210B, Die Cast, 5 disc tumbler. 2 keys No. M1054B. No. 210S, Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 210Y, Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Cast Iron, 2 1/4" x 3 1/8" x 1". Narrow 2 1/8" backset. Brass turnknob. Reversible. Cast Iron bolt, brass plated. For doors 1 1/4" to 2 1/2" thick. Operation — From outside by key, from inside by knob. Bolt may be held back by stop in case.	30	42
No. 250	No. 250 Black Wrinkle	Cylinder — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Cast Iron, 2½" x 2¾" x 1". Short 1½" backset. Brass turnknob. Reversible. Cast Brass bolt. For doors 1½" to 2½" thick. Operation — From outside by key, from inside by knob. Bolt may be held back by stop in case.	30	42

ILCO NIGHT LATCHES - DEADLOCKS - JIMMYPROOF LOCKS

ТҮРЕ	NUMBER & FINISH	DESCRIPTION	PER CASE	WGT. LBS.
No. 241B	No. 241B Gold Bronze Wrinkle	Cylinder — Die Cast, 5 disc tumbler, 2 keys No. 1054LB. Case — Cast Iron, 21/4" x 31/8" x 7/8". Narrow 21/8" backset. Brass turnknob. Reversible. Cast Iron bolt, brass plated. For doors up to 15/8" thick. Operation — From outside by key, from inside by knob. Bolt may be held back by stop in case.	30	40
Nos. 203, D203, 203C, D203C	No. 203 No. D203 Black Wrinkle No. 203C No. D203C Gold Bronze Wrinkle	Cylinder — 203, 203C, Solid Brass, 5 pin tumbler, 2 keys No. X1054K. D203, D203C, Die Cast, 5 pin tumbler, 2 keys No. X1054F. Case — Cast Iron, 2½" x 3½" x 1". Standard 2½" backset. Brass turnknob. Reversible. Solid Brass bolt, ½" throw. For doors 1½" to 2½" thick. Operation — From outside by key, from inside by knob.	30	55
Nos. 6391C D6391C	No. 6391C No. D6391C Gold Bronze Wrinkle	Cylinder — 6391C, Solid Brass, 5 pin tumbler, 2 keys No. X1054K. D6391C, Die Cast, 5 pin tumbler, 2 keys No. X1054F. Case — Cast Iron, 3" x 3½" x 1¼". Standard 2¾" backset. Brass turnknob. Reversible. Die Cast bolt, reinforced with two hardened steel, saw proof inserts, 1" throw. For doors 1¼" to 2½" thick. Operation — From outside by key, from inside by knob.	30	65
Nos. 401, D401, D401Y	No. 401 Dull Bronze No. D401 Sprayed Bronze No. D401Y Polished Bronze	Cylinder — 401, Solid Brass, 5 pin tumbler, 2 keys No. X1054K. D401, D401Y — Die Cast, 5 pin tumbler, 2 keys No. X1054F. Case — Die Cast, 2 ½ " x 4½" x ½". Backset, 2½" for doors opening in. Bronze turnknob. Reversible. Die Cast bolt. For doors 1 ¼ " to 2½" thick. Operation — From outside by key, from inside by knob.	12	24
No. 401C	No. 401C Dull Bronze	Cylinders — Two Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Die Cast, 2 % " x 4 ½" x % ". Backset, 2 ½" for doors opening in. Reversible. Die Cast bolt. For doors 1 ¼ " to 2 ½ " thick. Operation — By key either side.	12	33
No. 466B	No. 466B Natural Bronze	Cylinder — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Cast Bronze, 2 ½ " x 4 ½ " x 1½6". Backset 2 ½ " for doors opening in. Bronze turnknob. Features automatic shutter which closes spindle hole for maximum security. Reversible. Forged bronze bolt. For doors 1 ½ " to 2 ½ " thick. Operation — From outside by key, from inside by knob.	12	30
No. 466C	No. 466C Natural Bronze	Cylinders — Two Solid Brass, 5 pin tumbler, 2 keys No. X1054K. Case — Cast Bronze, 2 ½ " x 4 ½ " x 1½6". Backset 2 ½ " for doors opening in. Features automatic shutter which closes spindle hole for maximum security. Reversible, Forged bronze bolt. For doors 1 ¼ " to 2 ½ " thick. Operation — By key either side.	12	39


ILCO GARAGE DOOR LOCKS

ТҮРЕ	DESCRIPTION	PER CASE	WGT. LBS.
	WITH HOLD-BACK FEATURE CYLINDER No. 246 — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. No. 247 — Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 248 — Die Cast, 5 disc tumbler, 2 keys No. M1054B. OPERATION — From outside by key, from inside by knob. Bolt may be held retracted by knob from inside. FINISH — Black Wrinkle.	30	3 <i>7</i>
with Hold-Back Feature Nos. 246, 247, 248 without Hold-Back Nos. 243, 244, 245	WITHOUT HOLD-BACK CYLINDER No. 243 — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. No. 244 — Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 245 — Die Cast, 5 disc tumbler, 2 keys No. M1054B. OPERATION — From outside by key, from inside by knob. FINISH — Black Wrinkle. MATERIALS—DIMENSIONS — Case, Cast Iron, 2 1/4" x 3 1/8" x 1". Backset, 2 1/8". Bolt, Cast Iron, brass plated. Turnknob, brass. For doors 1 1/4" to 2 1/2" thick.	30	37
	WITH AUTOMATIC HOLD-BACK CYLINDER No. 236 — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. No. 237 — Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 238 — Die Cast, 5 disc tumbler, 2 keys No. M1054B. OPERATION — From outside by key, from inside by finger bolt. Hold-back catch engages automatically for one-hand operation. FINISH — Bright zinc. WITH MANUAL HOLD-BACK CYLINDER	30	1 <i>7</i>
with Automatic Hold-Back Nos. 236, 237, 238 with Manual Hold-Back Nos. 226, 227, 228 without Hold-Back Nos. 233, 234, 235	CYLINDER No. 226 — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. No. 227 — Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 228 — Die Cast, 5 disc tumbler, 2 keys No. M1054B. OPERATION — From outside by key, from inside by finger bolt. Hold-back catch is manually operated. WITHOUT HOLD-BACK CATCH CYLINDER No. 233 — Solid Brass, 5 pin tumbler, 2 keys No. X1054K. No. 234 — Die Cast, 5 pin tumbler, 2 keys No. X1054F. No. 235 — Die Cast, 5 disc tumbler, 2 keys No. M1054B. OPERATION — From outside by key, from inside by finger bolt. FINISH — Bright zinc. MATERIALS—DIMENSIONS — Case, Wrought Steel, 2" x 3 ¼". Backset, 2 ½". Bolt, Wrought Steel, zinc plated. For	30	17

ILCO MISCELLANEOUS LOCKS

ТҮРЕ	DESCRIPTION	PER CASE	WGT. LBS.
No. 4068 4068PB	GENERAL PURPOSE, CABINET AND DRAWER LOCK No. 4068 Dull brass finish No. 4068PB Bright brass finish CYLINDER: Die cast, 5 disc tumbler [†] , 250 changes, 2 Keys, No. M1054B. MATERIALS: Case, die cast. Bolt, steel. OPERATION: By 180° turn of key.	12	2 3/4
No. 4054	GENERAL PURPOSE, CABINET AND DRAWER LOCK No. 4054 Dull brass finish CYLINDER: Die cast, 5 disc tumbler [†] , 250 changes, 2 Keys, No. M1054B. MATERIALS: Case, brass plated, die cast housing. Bolt, die cast. OPERATION: By 180° turn of key.	12	3
No. 4750	WOOD LOCKER, COIN MACHINE LOCK No. 4750 Bright nickel finish CYLINDER: Die cast, 6 disc tumbler [†] , 3000 changes. 2 Keys, No. 1054P double bitted. MATERIALS: Cam, steel, cadmium plated. Spur Washer, steel, cadmium plated. Nut, steel, cadmium plated, 34" x 28 thread. OPERATION*: By 90° turn of key to the right. Key removable in locked position only.	12	3
No. 4750Y	GUN CASE, COIN MACHINE LOCK No. 4750Y Bright nickel finish CYLINDER: Die cast, 6 disc tumblert, 3000 changes. 2 Keys, No. 1054P double bitted. MATERIALS: Offset Cam, steel, cadmium plated. Spur Washer, steel, cadmium plated. Nut, steel, cadmium plated, 3/4" x 28 thread. OPERATION*: By 90° turn of key to the right. Key removable in locked position only.	12	3
Spur Washer No. 117 Cylinder Ring No. 121 No. C8605	CAM LOCKS FOR METAL OR WOOD PANELS Nos. C8405, C8505, C8605 Finish — 32, Bright stainless steel CYLINDER: Die cast, 5 disc tumbler, 250 changes. 2 Keys, No. H1054L. MATERIAL: Cam, steel, cadmium plated. Spur Washer, steel, cadmium plated. Cylinder Ring, brass, chrome plated. OPERATION: Packed with two stop washers which can be applied to give 90° turn, right or left with key removable in locked position only; or 180° turn, right or left with key removable in locked and unlocked position. For wood panel — Suffix Spur Washer and/or Cylinder Ring number to item number thus, C8505x117x121xfin.	12	2 1/2

ILCO PADLOCKS



SOLID BRASS — PIN TUMBLER

Material: Case, solid forged brass.

Finish: Natural brass, satin finish.

Shackle: Steel or Brass (see below). Steel

shackles are case hardened, bright

zinc plated.

Mechanism: Nos. 382, 382B four pin

tumbler. All others five pin tumbler.

Key Changes: Nos.382, 382B-1600 changes. Others practically unlimited.

Keys: Two, brass.

*Masterkeying: Can be master keyed in

groups, or keyed alike.

	C	ASE		SHACK	LE	† Available	Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	with chain	Blank No.	Per Box	Per Box
382	11/8"	1 1/8 "	Steel	7/32 "	9/16"	Steel	X1054JK	12	3 lbs
382B	11/8"	11/8"	Brass	7/32 "	9/16"	Brass	X1054JK	12	3 lbs
383	11/2"	15/16"	Steel	9/32"	7/8 "	Steel	X1054JA	12	51/8 lbs
383A	11/2"	15/16"	Steel	9/32"	11/2"	Steel	X1054JA	12	51/4 lbs
383B	11/2"	15/16"	Brass	9/32"	7/8 "	Brass	X1054JA	12	51/8 lbs
383N	11/2"	15/16"	Steel	9/32"	2"	Steel	X1054JA	6	25/8 lbs
383NB	11/2"	15/16"	Brass	9/32"	2"	Brass	X1054JA	6	25/8 lbs
383W	11/2"	15/16"	Steel	9/32"	21/2"	Steel	X1054JA	6	25/8 lbs
383WB	11/2"	15/16"	Brass	9/32"	21/2"	Brass	X1054JA	6	25/8 lbs
384	13/4"	15/8"	Steel	11/32"	1"	Steel	X1054K	6	41/8 lbs
384A	13/4"	15/8"	Steel	11/32"	2"	Steel	X1054K	6	45/8 lbs
384B	13/4"	15/8"	Brass	11/32"	1 "	Brass	X1054K	6	41/8 lbs
385	2"	15/8"	Steel	3/8 "	15/16"	Steel	X1054K	6	51/8 lbs
385B	2"	1 5/8 "	Brass	3/8 "	15/16"	Brass	X1054K	6	51/8 lbs

SOLID BRASS — DEADLOCKING TYPE

Material: Case, solid forged brass.

Finish: Natural brass, satin finish.

Shackle: Steel or Brass (see below). Steel shackles are case hardened, bright

zinc plated.

Mechanism: Deadlocking type. Double locking bolt. Nos. 352, 352B four pin tumbler. All others

five pin tumbler. Key may be removed in locked position only.

Key Changes: Nos. 352,352B-1600 changes. Others practically unlimited.

Keys: Two, brass.

*Masterkeying: Can be master keyed in groups, or keyed alike.

No.	C. Width	ASE Height	Metal	SHACKLE Metal Dia. Opening		†Available with chain	Key Blank No.	Packing Per Box	Weight Per Box
352	11/8"	11/8"	Steel	7/32 "	5/8 "	Steel	X1054JK	12	3 lbs
352B	11/8"	11/8"	Brass	7/32"	5/8 "	Brass	X1054JK	12	3 lbs
353	11/2"	11/4"	Steel	9/32"	13/16"	Steel	X1054JA	12	5 lbs
353B	11/2"	11/4"	Brass	9/32"	13/16"	Brass	X1054JA	12	5 lbs
353WB	11/2"	11/4"	Brass	9/32"	21/2"	Brass	X1054JA	6	25/8 lbs
354	13/4"	11/2"	Steel	11/32"	27/32"	Steel	X1054K	6	4 lbs
354B	13/4"	11/2"	Brass	11/32"	27/32"	Brass	X1054K	6	4 lbs

†PADLOCKS WITH CHAIN



Any of above padlocks can be furnished with 9 in. galvanized steel or brass chain (see above) attached to case by a clevis as shown. To specify in ordering, merely add $\frac{1}{2}$ to number, thus: $382\frac{1}{2}$ or $382\frac{1}{2}$ B.

PADLOCKS TO GOVERNMENT SPECIFICATIONS

GOVERNME	NT SPECIF	ICATION NO	D. FF-P-101C								
Gov't.		Ilco	Gov't.		llco	Gov't.		llco	Gov't.		llco
Type	Size	No.	Туре	Size	No.	Туре	Size	No.	Туре	Size	No.
EPB	11/8"	382	EPB	11/2"	383	EPB	13/4"	384	EPB	2"	385
†EPB	11/8"	3821/2	TEPB	11/2"	3831/2	TEPB	1 3/4 "	3841/2	†EPB	2"	3851/2
EPE	11/8"	382B	EPE	11/2"	383B	EPE	13/4"	384B	EPE	2"	385B
TEPE	11/8"	3821/2 B	† EPE	11/2"	3831/2 B	†EPE	13/4"	384½ B	†EPE	2"	385½ B
†With Ch	ain										
			IO. MS35647 h government	specificati	ons						
MS35647-1		3521/2B	MS35647-3	_	3531/2 B	MS35647-5	_	353½ WB	MS35647-7	_	354½B
MS35647-2	-	352B	MS35647-4	-	353B	MS35647-6	_	353WB	MS35647-8	-	354B
GOVERNME	NT SPECIF	ICATIONS N	IO. MIL-P-17	302							
Stamped "U.	S." in acc	ordance with	government	specificati	ons						
I	11/8"	382B	I	11/2"	383B	II	11/8"	3821/2 B	II	11/2"	3831/2 B

ILCO PADLOCKS

CAST BRONZE - PIN TUMBLER

Material: Case and insert, heavy cast

bronze.

Finish: Natural bronze, satin finish.

Shackle: Steel, case hardened, bright zinc plated. (Except Nos. 309B and 310B which have solid brass

shackle.) Locks both toe and heel.

Mechanism: Five pin tumbler. Double

locking rotary bolt.

Key Changes: Practically unlimited.

Keys: Two, brass.

Keys: Two, brass.

*Masterkeying: Can be master keyed in

groups, or keyed alike.

PADLOCKS WITH LOOSE RIVETS

All above padlocks can be furnished with loose rivets for the convenience of the locksmith in changing combinations, masterkeying, etc. In such cases, lock serial number is omitted and blank keys are furnished. When ordering, specify 309 x loose rivets, etc. Prices on request.

	CASE		SHACKLE			† Available	Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	with chain	Blank No.	Per Box	Per Box
309	13/4"	13/4"	Steel	5/16"	1"	Steel	X1054K	6	4 lbs
309A	13/4"	13/4"	Steel	5/16"	27/16"	Steel	X1054K	6	4 1/2 lbs
309B	1 3/4 "	13/4"	Brass	5/16"	1"	Brass	X1054K	6	4 lbs
310	2"	13/4"	Steel	3/8"	13/16"	Steel	X1054K	6	5 lbs
310A	2"	13/4"	Steel	3/8 "	21/2"	Steel	X1054K	6	51/4 lbs
310B	2"	13/4"	Brass	3/8 "	13/16"	Brass	X1054K	6	5 lbs

SOLID BRASS - PIN TUMBLER

Material: Case, solid forged brass.

Finish: Natural brass, satin finish.

Shackle: See below. Steel shackles are

case hardened, bright zinc plated.

*Masterkeying: Can be master keyed in groups, or keyed alike.

Key Changes: Practically unlimited.

Mechanism: Five pin tumbler.

	C	ASE		SHACK	LE	†Available	Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	with chain	Blank No.	Per Box	Per Box
373	11/2"	1 3/8 "	Steel	9/32"	7/8 "	Steel	X1054JA	12	41/2 lbs
373A	11/2"	13/8"	Steel	9/32"	11/2"	Steel	X1054JA	12	43/4 lbs
373B	11/2"	13/8"	Brass	9/32"	7/8 "	Brass	X1054JA	12	41/2 lbs
373N	11/2"	13/8"	Steel	9/32"	2"	Steel	X1054JA	6	23/4 lbs
373NB	11/2"	13/8"	Brass	9/32"	2"	Brass	X1054JA	6	23/4 lbs
373W	11/2"	13/8"	Steel	9/32"	21/2"	Steel	X1054JA	6	3 lbs
373WB	11/2"	13/8"	Brass	9/32"	21/2"	Brass	X1054JA	6	3 lbs

MARINE PADLOCK PROMOTION

No. 60MPA — Padlock Nos. 382B, 384B, 373B, 373NB, 373WB, 373½WB are available packed three of each, plus a point of-purchase display, in a carton. See Marine Padlock Display on page 39. Weight per carton 9 $\frac{1}{3}$ lbs.

†PADLOCKS WITH CHAIN

Any of above padlocks can be furnished with 9 in. galvanized steel or brass chain (see above) attached to case by a clevis as shown. To specify in ordering, merely add 1/2 to number, thus: 3821/2 or 3821/2B.

WROUGHT STEEL CASE - PIN TUMBLER

Material: Wrought Steel case, bolt and operating cam. Phosphor bronze

springs. Insert, special cast alloy.

Finish: Case, synthetic brass. Base, brass plated.

Shackle: Steel, case hardened and bright zinc plated. Locks both toe and


heel.


Mechanism: Four pin tumbler. Double locking rotary bolt.

Key Changes: 1600. Keys: Two, brass.


*Masterkeying: Can be master keyed in groups, or keyed alike.

	C	ASE		SHACKLE		Key	Packing	Weight
No	. Width	Height	Metal	Dia.	Opening	Blank No.	Per Box	Per Box
317	11/2"	15/16"	Steel	1/4 "	7/8 "	B1054	12	41/2 lbs
317	A 1½"	15/16"	Steel	1/4 "	11/2"	B1054	12	43/4 lbs
317	E 1½"	15/16"	Steel	1/4 "	21/2"	B1054	6	21/2 lbs





ILCO PADLOCKS



DIE CAST CASE - PIN TUMBLER

Material: Case, special cast alloy of high

Shackle: Steel, case hardened, bright zinc

plated. Locks both heel and toe.

tensile strength.

Color: Gun metal gray.

Mechanism: 5 Pin tumbler. Double locking

rotary bolt.

Key Changes: Practically unlimited.

Keys: Two, brass.

Masterkeying: Can be master keyed in

groups, or keyed alike.

SERVICE FEATURE — Back out set screw to release retaining-pin. Entire lock mechanism can be pushed out for servicing, master-keying, etc.

	C	ASE	SHACKLE			Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	Blank No.	Per Box	Per Box
390	11/2"	17/16"	Steel	1/4 "	7/8 "	1154G	12	4 lbs
391	1 3/4 "	1 5/8 "	Steel	5/16"	1 "	1054F	6	3 lbs

PLYLOK - LAMINATED PADLOCKS

Material: Case, laminated steel. Finish:

Cadmium Plated.

Shackle: Steel, case hardened, bright zinc plated. Locks both heel and toe, except

the ward type which locks on toe only. Mechanism:

No. 343, 4 pin tumbler. No. 344, 5 disc. tumbler No. 346, ward type.

Keys:

Two.

16.

Masterkeying:

Key Changes:

No. 343, can be master

No. 343, 1600 changes.

No. 344, 200. No. 346,

keyed in groups. All can

be keyed alike.

	C	ASE	S	SHACKLE		Key	Packed	Weight
No.	Width	Height	Metal	Dia.	Opening	Blank No.	Per Box	Per Box
343	11/2"	15/16"	Steel	%32 ["]	1"	X1054JK	12	51/2 lbs.
344	11/2"	15/16"	Steel	9/32"	1"	M1054B	12	51/4 lbs.
346	11/2"	1"	Steel	9/32"	1"	1286	12	5 lbs.

DIE CAST CASE — DISC TUMBLER

Material: Case, special cast alloy of high

tensile strength. Phosphor bronze

springs.

Finish: Nos. 320G, 320GA Green Case;

320SBUB, silver bronze.

Shackle: Steel, bright zinc plated.

gold bronze nameplate. Nos. 320S,

Mechanism: Five disc tumbler, non-spill type.

Key Changes: 200.

Keys: Two, aluminum.

Masterkeying: Not furnished master keyed.

Can be furnished keyed

alike.

	CASE			HACKLE		Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	Blank No.	Per Box	Per Box
320G	11/2"	11/2"	Steel	1/4 "	3/4 "	M1054B	12	41/2 lbs
320GA	11/2"	11/2"	Steel	1/4 "	11/2"	M1054B	12	45/8 lbs
3205	11/2"	11/2"	Steel	1/4 "	3/4 "	M1054B	12	41/2 lbs
20SBUB.	11/2"	11/2"	Steel	1/4 "	3/4 "	M1054B	6	21/4 lbs

PLASTIC BUBBLE PACKAGING

The popular No. 320SBUB. Padlock described above is available packed with keys in a clear plastic "bubble" for self-service merchandising. The bubble permits clear visibility of the product, creates impulse sales, increases turnover.

DIE CAST CASE - DISC TUMBLER

Material: Case, special cast alloy of high tensile strength.

Finish: Nos. 324, 324BUB. Green case;

Bright chrome.

gold bronze nameplate. No. 324C

Shackle: Steel, case hardened, bright zinc plated.

Mechanism: Five disc tumbler, non-spill

type.

Key Changes: 200. Keys: Two, brass.

Masterkeying: Not furnished master keyed.

Can be furnished keyed

alike.

	C	ASE	SHACKLE			Key	Packing	Weight
No.	Width	Height	Metal	Dia.	Opening	Blank No.	Per Box	Per Box
324	15/16"	1"	Steel	3/16"	17/32"	1154C	12	13/4 lbs
324C	15/16"	1"	Steel	3/16"	17/32"	1154C	12	1 3/4 lbs
324BUB.	15/16"	1"	Steel	3/16"	17/32"	1154C	6	₹ Ibs

PLASTIC BUBBLE PACKAGING


This small, all purpose padlock No. 324BUB. described above is available packed in a clear plastic "bubble" for self-service merchandising. Popular for mail boxes, bags, chests, etc. Ideal for impulse sales and increased profits.

DEADLOCKS, MORTISE BOLTS, SECRET GATE CATCH

ITEM	NUMBER AND DESCRIPTION	FINISHES	PER CASE	WGT. LBS.
No. A22141/2	LOCKWOOD MORTISE DEADLOCKS For doors 1 \%" to 1 \%" thick No. A2214 Has cylinder outside only. No. A2214 \% Has cylinder outside, turnknob inside. No. A2214 \% Has cylinders both sides. Case, cast iron, 2 \%\%" x 1 \%\%" x 1 \%\%" Front, brass armored, 4 \%" x 1 \%\%" fat. Bolt, brass, 1 \%\%" throw. Backset, 2 \%\%". Brass turnknob. Cylinder, brass, 5 pin tumbler with two keys No. B308. Can be masterkeyed with other Lockwood locks having No. B308 key. Can be keyed alike. Add symbol KA. Reversible.	3 Bright Brass 10 Dull Bronze 26D Dull Chrome	12	22 23 26
No. 2221	LOCKWOOD TUBULAR DEADLOCKS For doors 1 % " to 1 ¾ " thick No. 2220 Has cylinder outside only. No. 2221 Has cylinder outside, turnknob inside. No. 2222 Has cylinders both sides. Case, wrought steel, dichromated, 15/16" x 3¾6". Front, brass, 2¼" x 1". Bolt, brass, ½" throw. Backset, 2¾". Cylinder Collar, brass, 2½" dia. Projects 15/16". Brass turnknob. Cylinder, brass, 5 pin tumbler with two keys No. B308. Can be masterkeyed with other Lockwood locks having No. B308 key. Can be keyed alike. Add symbol KA. Reversible.	3 Bright Brass 10 Dull Bronze 26D Dull Chrome	30	30 32 36
No. 5055	No. 5055 ILCO MORTISE BOLT For doors 1 %" to 1 34" thick Operation — By turnknob one side only. Case, wrought steel, dichromated, 15/16" x 33/16". Front, brass, 2 ½" x 1". Bolt, brass, ½" throw. Backset, 2 %". Brass turnknob. Universal. One per box.	3 Bright Brass 10 Dull Bronze 26 Bright Chrome 26D Dull Chrome	12	3
No. 5050	No. 5050 ILCO MORTISE BOLT For doors 1" to 21/8" thick Operation — By turnknob one side only. Case, wrought brass, 5/8" x 215/16". Front, 11/16" dia. Bolt, steel, plated 1/2" dia. 5/8" throw. Backset, 2". Turnknob, die cast, plated. Universal. Six per box.	4 Dull Brass	144	37
No. 5051	No. 5051 ILCO LOCKING MORTISE BOLT For doors 11/4" to 13/4" thick Operation — By key outside ONLY. Case, wrought brass, 5/8" x 215/16". Front, 11/16" dia. Bolt, steel, plated, 1/2" dia. 5/8" throw. Outside plate, die cast, 23/8" x 11/4". Inside plate, steel, 23/8" x 11/4". Backset, 2". Cylinder, die cast, 5 disc tumbler. Two keys No. M1054B. Can be keyed alike. Add symbol KA to number. One per box.	4 Dull Brass	60	25
Secret Gate Catch No. GL11	No. G11 ILCO SECRET GATE CATCH Operation — Pressure on trip, under case, retracts latch bolt. Case, cast iron 21/8" x 21/2" x 11/16". Strike, 21/8" x 7/8" x 11/16". Cast iron bolt, brass plated. Brass knob. One per box.	Gold Bronze Wrinkle	12	7

ILCO "50" SERIES DOOR CLOSERS

STANDARD INSTALLATION ON FLUSH SIDE OF DOOR



FEATURES:


Versatile Closer — Modern Design. Its sturdy streamlined case contains a rugged, precision-built mechanism for most efficient door control.


Heavy Compression Spring — Ample Power. Designed to provide sufficient power for dependable performance, yet to allow easy opening of door. Checking action simultaneously controls the spring power upon release of opened door and prevents unexpected quick closing swing regardless of the angle of opening.

Single Valve Gives Dual Speed Control. Full turns of the valve controls the closing speed to the latch. Fractional turns control latching speed.

Hand — Non Holder Arm Closers only, can be installed on right or left hand doors without change, by alternate application of arm to closer. Closers with holder arms are handed and must be ordered for right or left hand application.









PRECISION BUILT — HIGHEST QUALITY MATERIAL

Case: Sturdy cast iron alloy.

Arms: Dropped forged steel for high tensile strength and resistance to

bending.

Rack: Precision broached to close tolerance to ensure efficient checking

action.

Pinion: Heat treated alloy steel to minimize wear and maintain the close

tolerance.

Spring: Highly tempered chrome silicon alloy, cold set and peened to increase

fatigue resistance.

Climatic For good lubrication and minimum wear. Non-Gumming and main-

Liquid: tains its viscosity under extremes of temperature.

90°-125° HOLDER ARM

The automatic holding mechanism at the joint of the main and forked arms can be adjusted to hold the door open at any desired degree of opening up to 125°. In ordering, state hand. Example: A15ORH.

Closer Nos.				Average
*With Non- Holder Arm	With 90°-125° Holder Arm	For Door Size	Packed Per Case	Weight Per Case
A50	A150	2'2" x 7'	6	38
B50	B150	2′6″ x 7′	6	40
C50	C150	3′0″ x 7′	6	46
D50	D150	3′6″ x 7′	6	47

Above closers require minimum top rail 11/2" wide.

"50" SERIES BRACKET

No. 854 — For installation of "50" Series Closers on recessed side of door when overhead surface door holders are also used.

*Regularly furnished with 9'' arms which permit opening to 125° . Can be furnished with 11'' arms to order, permitting opening up to 140° . To specify closer with 11'' arms order thus: C50 x 11''.

ILCO "50" SERIES DOOR CLOSERS

PARALLEL ARM INSTALLATION ON RECESSED SIDE OF DOOR

When closers are to be installed on recessed side of door, but the lack of sufficient headroom makes the use of a bracket undesirable, parallel arm closers may be used. In this application, the closer is attached directly to the recessed side of door and the arms stand parallel to the door when closed. Thus, when door is swung open, the closer is carried out of the opening, leaving headroom free.

90°-125° HOLDER ARMS

The automatic holding mechanism at the joint of the main and forked arms can be adjusted to hold the door open at any desired degree of opening up to 125°. In ordering, state hand. Example: A1150RH.



90°-180° HOLDER ARMS

Where door is to be held open at any point between 125° - 180° a slightly different arm is provided. The holding device is located at the joint of the arm and soffit bracket. In ordering, state hand. Example: A1250RH.

90°-180° FUSIBLE LINK HOLDER ARM

Designed to release the holding mechanism and automatically cause the door to close in case of fire. A link of fusible metal retains the frictional holding members in operating position in normal temperatures. When the temperature rises to 160° the link fuses, releasing the hold-open mechanism and the door quickly closes under power of the spring. In ordering, state hand. Example: C2350RH.

	CLOSER NOS.					
*With Non- Holder Arm	With 90°-125° Holder Arm	With 90°-180° Holder Arm	With Fusible Link Arm	DOOR SIZE	Packed Per Case	Average Weight Per Case
A850	A1150	A1250		2'2" x 6'6"	6	39
B850	B1150	B1250		2'2" x 7'	6	41
C850	C1150	C1250	C2350	2'6" x 7'	6	47
D850	D1150	D1250	D2350	3′0″ x 7′	6	48

^{*}Permits opening to 180°.

All above closers require minimum top rail 23/4" wide, plus thickness of stop.









FINISHES: Regularly furnished in Silver Bronze (SB). Can also be furnished Sprayed Dull Bronze (BZ), or Brown Lacquer (BL), when so specified. To order merely add finish symbol to number. Example: No. A850BZ.


HOW TO ORDER: Select sizes of closer desired for various types and sizes of doors from tables above. Give specific closer number to indicate size and type of arm. Specify finish if other than standard SB. Specify each size in case quantities as shown above. Furnished with wood and machine screws.


ILCO UNIVERSAL DOOR CLOSERS











FOR RIGHT OR LEFT HAND DOORS WITHOUT CHANGE

FEATURES:

Helical Coil Spring which permits the use of an entirely automatic reversing mechanism, so that the closer is ready for right or left hand doors without change.

Forged Steel Crankshaft is a heavy one-piece alloy-steel, drop forged to withstand severe usage.

Precision-Fit Piston for dependable checking action.

Welded Steel Link joining the piston to the crankshaft.

Combination Packing Nut and Gland eliminates leakage.

One Control Valve regulates both closing and latching speeds.

CLOSER NUMBERS WITH REGULAR ARMS

Numbers		Door Size	Door Size (Maximum)		
With Non- Holder Arm	With 90°-135° Holder Arm	Exterior	Interior	Packed Per Case	Average Weight Per Case
21	-	Screen or Storm door 1 1/8" x 2'6" x 6'6"	1 3/8" x 2'6" x 6'6"	6	42 lbs.
22	_	Screen or Storm door 1 3/8" x 2'8" x 7'0"	1 %" x 3'0" x 7'0"	4	41 lbs.
23	123	1 3/4" x 2'6" x 7'0"	1 3/4" x 3'4" x 7'0"	4	50 lbs.
24	124	21/4" x 3'0" x 7'6"	2 1/4" x 4'0" x 7'6"	4	62 lbs.
25	125	Extra heavy or subjec	to strong drafts	4	83 lbs.

WITH PARALLEL ARM FOR INSTALLATION TO RECESSED SIDE OF DOOR — WITHOUT BRACKET

In this installation the closer is attached directly to the recessed side of the door and the arms stand parallel to the door when closed. Thus, when door is swung open, the closer is carried out of the opening, leaving headroom free.

CLOSER NUMBERS WITH PARALLEL ARMS (Arm is reversible)

Nun	Numbers Door Size		(Maximum)		
With Non- Holder Arm	With 90°-135° Parallel Holder Arm	Exterior	Interior	Packed Per Case	Average Weight Per Case
821	_		Extra light doors	6	42 lbs.
822	_	Screen or Storm door 1 1/8" x 2'6" x 6'6"	1 3/8" × 2'6" × 6'6"	4	41 lbs.
823	1123	1 %" x 2'8" x 7'0"	1 %" x 3'0" x 7'0"	4	50 lbs.
824	1124	1 3/4 " x 2'6" x 7'0"	1 3/4 " x 3'4" x 7'0"	4	62 lbs.
825	1125	2 1/4" x 3'0" x 7'6"	21/4" x 4'0" x 7'6"	4	83 lbs.

FINISHES — Regularly furnished Brown Lacquer finish. Can also be furnished Sprayed Dull Bronze (BZ), or Silver Bronze (SB), when so specified. To order, merely add finish symbol to number. Example: No. 23BZ.

ILCO BALL BEARING RACK AND PINION DOOR CLOSERS

FOR TOP PERFORMANCE — MINIMUM ATTENTION

FEATURES:

Permits Opening Door With Minimum Effort — Internal friction and resistance to opening is reduced to absolute minimum by the use of ball-bearings at the two main bearing points of the shaft.

Immediate Checking Control At Any Angle — Sturdy, one-piece precision made rack and pinion mechanism has no "dead center" and the spring power is simultaneously under control of the checking action upon release of the door.

Extra Power For Any Installation — Extra powered spring is capable of sufficient reserve force to close any door against the most extreme draft conditions.

Leakproof Construction — **All-Weather Liquid** — The packing gland design defeats the principle of capillary creeping and eliminates all leakage. Ilco's Climatic Liquid is unaffected by extreme temperature changes, is non-gumming and contributes much to trouble-free performance.

CLOSER NUMBERS WITH VARIOUS TYPE ARMS

	Types & Numbers		Types & Numbers		Door Size	(Maximum)		
With Non- Holder Arm	With 90°-135° Holder Arm	With Parallel Non- Holder Arm	With Parallel 90°-135° Holder Arm	Exterior	Interior	Packed Per Case	Weight Per Case	
B30	B130	B830	B1130	Screen or Storm 1 % " x 3'0" x 7'0"	1 3% " x 2'8" x 7'0"	4	48 lbs.	
C30	C130	C830	C1130	1 3/4" x 2'6" x 7'0"	1 3/4" x 3'4" x 7'0"	4	63 lbs.	
D30	D130	D830	D1130	2 1/4" x 3'0" x 7'6"	2 1/4" x 4'0" x 7'6"	4	75 lbs.	
E30	E130	E830	E1130	3" × 3'6" × 7'6"		4	110 lbs.	
F30	F130	F830	F1130	Extra heavy, refrige	ators, etc.	4	110 lbs.	

WITH PARALLEL ARM FOR INSTALLATION ON RECESSED SIDE OF DOOR — WITHOUT BRACKET

Where closers are to be installed on recessed side of door, but brackets are undesirable due to lack of sufficient headroom, parallel arm closers may be used. In this installation, the closer is attached directly to recessed side of door and the arms stand parallel to the door when closed. Thus when door is swung open, the closer is carried out of the opening, leaving headroom free.

FOR MOUNTING CLOSERS ON RECESSED SIDE OF DOOR

	For Clo		
Bracket Number	Universal	Ball-Bearing	Weight each
912	21 and 22		2 ½ lbs.
B893	23	В	2 ½ lbs.
C894	24	C	3 lbs.
D895	25	D	3 lbs.
E896		E and F	4 1/4 lbs.


FINISHES — Regularly furnished Brown Lacquer finish. Can also be furnished Sprayed Dull Bronze (BZ), or Silver Bronze (SB), when so specified. To order, merely add finish symbol to number. Example No. 912BZ.


HOW TO ORDER — Select sizes of closers desired for various types and sizes of doors from table above. Give specific closer number to indicate size and type of arm. Specify finish if other than standard Brown Lacquer. Specify each size in case quantities as shown above. Furnished with wood and machine screws.
















LOCKWOOD MAKES A FULL LINE OF PANIC EXIT DEVICES



ACCESSORIES




No. 68 — Strike regularly furnished with 90B Series Rim Devices for use on single doors. Cast bronze. Size 3 \%" x 1 \%". Projection \\ 3\%".

No. 45 — Mullion strike, adjustable type for use with 90B Series Rim Devices. Cast Bronze. Size 4 1/8 " x 1 1/4" adjustment.

STRIKES

No. 43 — Strike regularly furnished with 80B Series Mortise Lock Devices (non-stock). Cast bronze. Size 4 3/4 " x 1 1/2". Lip to center, 1 1/4". For single doors.

No. 66 — Strike used with 90B Series Rim Devices when used in combination with Vertical Rod Devices. Cast bronze. Size $3 \frac{1}{8}$ " x $1 \frac{3}{4}$ ".



REMOVABLE MULLION

No. 780 — Size 2%" x 2%". 8' long. Wrought steel. Permits the use of Rim Devices on a double door opening. Mullion may be easily removed at any time to permit passage of large objects. Finish — Prime Coat.

CO-ORDINATOR

No. 770 — Cast brass or bronze. Case size $13'' \times 1\frac{1}{2}'' \times \frac{8}{8}''$. For pairs of doors with over-lapping astragal, or rabbeted edge. Prevents active door from closing before inactive door. Can be mortised into stop or surface mounted as desired. Reversible for active door of either hand. Carry open finger, cast brass or bronze, size $1\frac{1}{2}'' \times 2\frac{3}{8}''$. Buffer plate, 1'' wide, $1\frac{1}{2}''$ long.



SEX BOLTS

For 70B Series — 16 per package.

For 80B and 90B Series — 8 per package.

Finishes — 10, Dull bronze and 26D, Dull chrome.

ROD EXTENSIONS

To increase rod length of 70B Series vertical rod devices when door height requires a rod longer than standard stock size.

Sizes — 2", 4", 6" lengths.

Finishes — 10 Dull bronze, 26D Dull chrome.

THESE DEVICES ARE IN STOCK FOR IMMEDIATE DELIVERY

RIM LOCK DEVICES — SS90B SERIES —



Furnished to fit doors 3'6" wide. Crossbar can be easily cut to fit doors of narrower width. Push on crossbar retracts latch at all times. Crossbar can be dogged down to permit pushpull operation of door.

WITH NO OUTSIDE TRIM



No. SS90B x Fin. x Hand For doors up to 3'6" wide and any thickness. Furnished with adjustable strike No. 68.

WITH PULL OUTSIDE



No. SS94B x Fin. x Hand For doors up to 3'6" wide and any thickness. Furnished with adjustable strike No. 68.

WITH THUMBLATCH AND CYLINDER OUTSIDE

Thumbpiece retracts latch except when locked by key.



No. SS92B x Fin. x Hand For doors up to 3'6" wide and $1\frac{1}{4}$ " to $1\frac{3}{4}$ " thick. Furnished with adjustable strike No. 68.

WITH PULL AND CYLINDER OUTSIDE



No. SS93B x Fin. x Hand For doors up to 3'6" wide and 1 1/4" to 1 3/4" thick. Furnished with adjustable strike No. 68.

VERTICAL ROD DEVICES — SS70B SERIES —



Furnished to fit doors 3'6" x 7'0". Crossbar and vertical rods can be cut to fit doors of smaller dimensions. Push on crossbar retracts top and bottom bolts at all times. Crossbar can be dogged down to permit push-pull operation of doors. See Rod Extensions, page 30.

WITH NO OUTSIDE TRIM



No. SS70B x Fin, x Hand For doors up to 3'6" x 7'0" and any thickness. Furnished with strikes Nos. 51 and 52.

WITH PULL OUTSIDE



No. SS74B x Fin. x Hand For doors up to 3'6" x 7'0" and any thickness. Furnished with strikes Nos. 51 and 52.

WITH KNOB AND CYLINDER OUTSIDE



Knob retracts top and bottom bolts, except when locked by key.

No. SS71B x Fin. x Hand

For doors up to 3'6" x 7'0" and 1 1/4" to 1 3/4" thick. Furnished with strikes Nos. 51 and 52.

CONCEALED VERTICAL ROD DEVICES — SS60C SERIES



Furnished to fit doors 3'6" x 7'0" having hollow stiles with internal dimensions not less than 1" wide and 1 %" thick. Crossbar and vertical rods can be cut to fit doors of smaller dimensions.

Push on-crossbar retracts top and bottom bolts at all times. Crossbar can be dogged down to permit push-pull action of door.

Furnished with Strike when specified.

See Mullions, opposite page.



No. SS60C x Fin. x Hand No outside trim



No. SS64C x Fin. x Hand With pull outside



No. SS61C x Fin. x Hand With pull *Tee-lever & Cylinder out.

*Tee-Lever retracts top and bottom bolts, except when locked by key.

FINISHES: Dull Bronze, symbol 10 — Dull Chrome, symbol 26D.

Right Hand Reverse Bevel, symbol RHRB. Left Hand Reverse Bevel, symbol LHRB.

IN ORDERING: Suffix symbols for Finish and Hand to catalog number.

EXAMPLE: No. SS90B x 10 x RHRB.



CYLINDERS - KEYING KITS



LOCKWOOD MORTISE LOCK CYLINDER 5 pin tumblers

No. 951 — Furnished in \%" length variation from 1" to 1\\'\2". See dimension "A" which indicates length. Solid Brass, standard diameter and thread. Included are two keys No. B308 and two rings 1/4" and 1/8" high. Can be furnished keyed alike, (symbol KA), or masterkeyed, (symbol MK) when so ordered. Indicate length when ordering. Example: 951x1 1/8".

Finishes — Regularly furnished 4 Dull Brass. Can also be furnished 3 Bright Brass, 10 Dull Bronze, or 28 Satin Aluminum at no extra charge; or 26 Bright Chrome and 26D Dull Chrome at an extra charge. Packed one per box, 12 per carton. Weight from 41/2 lbs. (1") to 71/2 lbs. (1 1/2").






LOCKWOOD RIM LOCK CYLINDER 5 pin tumblers

No. 956 — Includes two keys No. B308, one ring, back plate and two connecting screws. Solid Brass. Can be furnished keyed alike (symbol KA), or masterkeyed, (symbol MK) when so ordered.

Finishes — Regularly furnished 4 Dull Brass. Can also be furnished 3 Bright Brass or 10 Dull Bronze, at no extra charge; or 26 Bright Chrome and 26D Dull Chrome at an extra charge. Packed one per box, 120 per carton. Weight, 45 lbs.



ILCO MORTISE LOCK CYLINDERS

5 pin tumblers

Solid Brass, standard diameter and thread. Included are two keys No. X1054K and two rings 1/4" and 1/8" high.

No.	Size
No.	Dim. A
4001	1"
4001 1/2	1 1/8 "
4002	1 1/4 "
4002 1/2	1 3/8 "
4003	1 1/2 "

Finishes — Regularly furnished 4 Dull Brass. Can also be furnished 3 Bright Brass, 10 Dull Bronze, or 28 Satin Aluminum, at no extra charge; or 26 Bright Chrome and 26D Dull Chrome at an extra charge. Packed one per box, 12 per carton. Weight from $4\frac{1}{2}$ lbs. (1") to $7\frac{1}{2}$ lbs. (1 1/2").



ILCO RIM LOCK CYLINDERS

No. 4014 — Die cast, 5 disc tumbler. Two keys No. M1054B.

No. 4019 — Solid brass, 5 pin tumbler. Two keys No. X1054K.

No. 4038 — Die cast, 5 pin tumbler. Two keys No. X1054F.

All above complete with back plate, one ring and two connecting screws.

Finishes — 4014, 4038, 4 Dull Brass only. 4019 regularly furnished 4 Dull Brass. Can also be furnished 3 Bright Brass or 10 Dull Bronze at no extra charge; or 26 Bright Chrome and 26D Dull Chrome at an extra charge,

Packed — One per box, 120 per carton. Weight, 45 lbs.



ILCO ADJUSTABLE MORTISE LOCK CYLINDER Adjustable from 1 1/4" to 1 3/4" Solid Brass. Standard Diameter and Thread

No. Type Two Keys

Adjustable Ring No. 4058

Weight Dozen 5 1/4 lbs.

4004 5 pin tumbler

No. X1054K, brass

Packed one per box, 12 per carton. Finishes — Regularly furnished 4 Dull Brass. Can also be furnished 3 Bright Brass, 10 Dull Bronze or 28 Satin Aluminum at no extra charge; or 26 Bright Chrome or 26D Dull Chrome at an extra charge.

KEYING KITS



No. RK59 — For General Use

Contents — 1 gross each assorted Pins A115, B102, C095, D115, E102, F095, M115, M102, M095, and springs, 50, 50 $\frac{1}{2}$, 51. 1 gross each flat head Machine Screws, $\frac{1}{4}$ x 4-36, $\frac{5}{16}$ x 3-48. 1 gross round head Screws, $\sqrt{32}$ x 3-48. 1 dz. each Retainers No. 15, 20, 22. 1 Following Tool 19 Ft. 1 pair small Tweezers. Weight 1 3/4 lbs.

No. 930 - For "R", "S" and "D" Series Only

Contents — ½ gross each Bottom Pins Nos. 0, 1, 2, 3, 4, 5, 6, 7. 2 dz. each Master Pins Nos. 2, 3, 4, 5, 6, 7, 8, 9. 1/2 gross each Top Pins, sizes A, B, C. 1/2 gross Springs No. 364. 2 dz. Retainers. 6 only Pick-Emergency Keys. 1 Tweezer. 1 No. 19FT Following Tool. 1/2 dz. each Key Blanks Nos. B325 and B326. Weight, 1 1/2 lbs.

REPLACEMENT PARTS - TYKEES - MISCELLANEOUS LOCKS



ILCO ESCUTCHEONS

Wro	Jaht	Steel.	Plated
	3		
			D

No.	Size	Description
RP4	10" x 2 3/4"	Complete as shown, with thimble and keyhole. Spacing $3 \frac{1}{8}$ " (center of knob hole to center of key post hole).
RP3	10" x 2 3/4"	Has keyhole only. No thimble; or thimble hole.
RP2	10" x 2 3/4"	Has thimble and thimble hole (assembled). No keyhole.
RP1	10" x 2 3/4"	Has knob hole only. No thimble. No keyhole.
RP5	10" x 2 3/4"	Has no holes (except screwholes).
RP14	7" x 2 1/4"	Complete as shown, with thimble and keyhole. Spacing $2\frac{3}{16}$ " (center of knob hole to center of key post hole).
RP7	7" x 2 1/4"	Has thimble and turn knob.
RFI	1 1/8 " O.D. x 1/6" hole	Thimble only. Brass, dull finish.

All above escutcheons furnished with four 1" x 6 O.H. wood screws. Finish — 4 Dull brass.



ILCO DOOR KNOBS

Wrought Brass

No. KN3 One pair knobs with spindle and roses. No. KN4 One pair knobs with spindle, no roses.

Knob — 2" dia. Projection — 2 ½". Rose — No. R01, 2" dia.



No. KN1 One pair knobs with spindle and roses. No. KN2 One pair knobs with spindle, no roses.

Knob — 2 1/4" dia. Projection — 2 \%". Rose — No. R01, 2" dia.

Packed 6 pair per box, 60 pair per carton. Weight per carton 32 lbs. Finishes — 3 Bright Brass, 4 Dull Brass, 10 Dull Bronze, 26 Bright Chrome.



Wrought Steel Two Piece Top

No. KN5 One pair knobs with spindle and one rose.

One pair knobs with spindle, no roses. No. KN6

Projection — 2 3/8". Knob — 2 1/4" dia. Rose — 2" dia.

Packed: KN6-12 spindled pair per special compartmented carton. 48 pair per large carton. Weight 23 lbs. KN5 — one dozen per carton. Weight 51/4 lbs.

Finishes — KN6, 4 Dull Brass; KN5, Japanned.



ILCO KEYHOLE LOCK

Gives Pin Tumbler Security to Any Bit-Key Lock

No. 444 — Just push it into the keyhole of any bit-key lock, with hook up (after locking with regular key). Spring hook catches in lock case and LOCKS IN, blocking keyhole and preventing picking or unlocking with a skeleton key.

To remove from keyhole, merely insert key with smooth edge up, give key one-half turn and pull device out of keyhole.

Packed one dozen per box. Weight per box 3/4 lb.



TELEPHONE DIAL LOCK PROTECTION AGAINST UNAUTHORIZED TOLL CALLS

No. 4760 — Protects subscriber against unauthorized use of phone. Locks into first opening of dial, thereby prevents dialing number or operator. Can be furnished keyed alike. Regularly furnished 12 in clearview envelopes on attractive display card, lustrous hammertone lacquer finish.



LOCKWOOD TIE CLASP OR MONEY CLIP

No. 616B — An attractive personal accessory with a highly practical value. Whether used as a tie clasp or money clip, this is a usable key, when cut to fit a Lockwood lock with No. B308 or No. B325 key. This can be done on any key cutting machine. The gold plated key-clasp is mounted on a wine colored, simulated suede platform. The box sparkling clear plastic.

ILCO KEY CUTTING MACHINES



ULTRAMATIC . . . ILCO'S ANSWER TO THE "PUSH BUTTON AGE"

FOOLPROOF OPERATION -


The most revolutionary key cutting machine advance in twenty years — no guesswork, — everything is automatic — practically impossible to cut a key incorrectly. Cuts all cylinder keys, including the tricky 1307A double sided key.

PRECISION ADJUSTMENT SYSTEM — Ingenious gauge mechanism sets the guide to exactly the proper height in seconds.

MINIMUM MAINTENANCE — Never needs oil. Nylon to steel contact points, oil-impregnated bearings, eliminate need for lubrication.


LIGHTWEIGHT — Just 22 lbs. Pick it up by the built-in carrying handle and you are ready to go to a construction site or re-keying job and cut keys on the spot.

No. 185UM Complete with 110 Volt, 60 Cycle, Single Phase AC Motor, Cutter, Cord, Plug and operating instructions. Shipping weight 27 lbs.



FROM BLANK TO FINISHED KEY IN 6 EASY STEPS


- 1. Set cutter to proper width of key blank using width gauge at top of machine.
- With both knobs loose, insert sample key into right hand slot as far as it will go until shoulder of the key rests snugly against quide.
- 3. In same manner, insert key blank into left hand slot using cutter blade as a guide against the shoulder.
- 4. Tightening left hand knob secures both sample key and key blank in position.
- Push the switch and ULTRAMATIC does all the work automatically.
- 6. Once key has been cut, release left hand knob, take out key and remove burrs on the handy scrape plate on right leg.



"MONITOR" KEY CUTTING MACHINE

No. 184CD (without motor). No. 2184CD (with motor)

Simple, compact key duplicator for cylinder keys only. Features adjustable key guide; large thumb screws on key clamps for positive vise-like gripping; swivel type carriage; improved type rotary cutter and positive key gauge for accurate alignment. Motor for No. 2184CD is 1/20 H.P., 110 Volt, 60 Cycle, Single Phase AC, 1725 RPM. Weight, No. 184CD, 12½ lbs.; No. 2184CD, 29 lbs.



"IMPROVED MINUTE" KEY CUTTING MACHINE

No. 175IA (without motor), No. 2175IA (with motor)

Duplicates cylinder and flat steel keys. This machine is widely used where volume of key cutting is not heavy and runs largely to cylinder and flat steel keys. Included are one Rotary File No. 5RF for cylinder keys and one Rotary Slotter No. 3FS for flat steel keys. Motor for No. 2175IA is ½ H.P., 110 Volt, 60 Cycle, Single Phase AC, with switch, cord and plug. Mounted on base 17" x 12", ready to operate. Weight, No. 175IA, 28 lbs.; No. 2175IA, 59 lbs.

ILCO KEY CUTTING MACHINE OUTFITS

ROTARY KEY BLANK DISPLAY

Complete with 102 popular key blank numbers
No. 10KBA

This eye-catching, revolving display board is attractively finished with a dark blue background and yellow trim. It has six panels with 21 hooks on each panel (126 hooks in all). Each hook holds 1 dozen key blanks. On 5 panels the hooks are marked with a key blank number and the make of lock the key fits. These numbers correspond to the 59KBA key blank assortment consisting of $\frac{1}{2}$ dozen each of 102 of the most popular key blanks. The cylinder is 10'' dia. x $19\frac{1}{4}''$ high. It is furnished with a stand $10\frac{1}{2}''$ wide with two screw holes for fastening to counter. The entire assembly stands 34'' high and takes only 12'' x 12'' counter space.

Packed in individual carton complete with stand, pipe support, 126 hooks and 59KBA key blank assortment. Weight 30 lbs.

DISPLAY ONLY No. 2RKB

Same as No. 10KBA described above, but without key blanks.

Packed one per carton complete with stand, pipe support, and 126 hooks.

Weight 17 lbs.

"ULTRAMATIC" KEY MACHINE AND DISPLAY No. 4185UM (as illustrated)


Ultramatic key machine and the Ilco rotary key blank display described above, along with an assortment of quality Ilco key blanks. The key blank numbers correspond to the 59KBA assortment which consist of ½ dozen each of 102 most popular key blanks. The regular door lock key blanks are laid out alphabetically by make of lock on four panels. Automotive key blanks are all on the fifth panel and the sixth panel is left blank to allow for additions. Complete package consists of No. 185UM key machine, rotary display, complete with stand and 59KBA assortment. Weight 57 lbs.

"MONITOR" KEY MACHINE AND DISPLAY No. 5184CD (as illustrated)

This outfit consists of a rotary key blank display, No. 184CD "Monitor" key cutting machine complete with 110 Volt, 60 Cycle, Single Phase AC motor, mounted on a heavy cast iron base 13 5%" x 8 3%"; key blank assortment 59KBA which consists of one-half dozen each of 102 popular key blanks; 126 hooks with a capacity for one dozen key blanks each. Shipping weight complete 63 lbs.

No. 3184CD


Same as No. 5184CD, except that no key blanks are included. Shipping weight complete 50 lbs.



MERCHANDISERS

No. DP57 LOCK MERCHANDISER
"IMPULSE SALES" INCREASE VOLUME ON 24 STANDARD STOCK ITEMS





INCLUDES ONE EACH OF THE FOLLOWING ITEMS

Cat.

No.

Description

LEFT PANEL (Left to right)

210B 2 1/8 " B.S. Night Latch D220 Standard Night Latch 219C Night Latch

263GY Night Latch Streamlatch

D401 Jimmyproof Deadlock

203C Deadlock

CENTER PANEL (Left to right)

1 ½" Disc Tumbler Padlock 1" Disc Tumbler Padlock 320G 324 1 ½" Pin Tumbler Padlock 390 1 3/4 " Pin Tumbler Padlock 391 1 1/2" Brass Padlock 373 Long Shackle Padlock 1 ¾ ″ Brass Padlock 373A 384 2" Brass Padlock 385 4054 Desk Lock 4068 Cabinet Lock KN1x3 Brass Knob

KN6x4 Steel Knob, brass plated

RIGHT PANEL (Top to bottom)

2221x3 Tubular Mortise Deadlock
MD6204x4 Bit Key Inside Lockset
444 Keyhole Lock

RT110x3 Cylindrical Passage Lockset
RT120x3x26 Cylindrical Privacy Lockset
RT130x3 Cylindrical Entrance Lockset

COLORFUL

The revolving wing panels are a brilliant, eye catching red. The center panel is a lustrous navy blue. Base and frame are attractive hardwood, finished in gleaming natural color. The sign is done in red, yellow, blue and white.

Against this colorful backdrop the sparkling finishes of the products present a most compelling appeal.

COMPACT

As shown in the inset, the 24 products displayed have been arranged to require a surprisingly small space — actually less than two square feet of counter space. The base is $40'' \times 6''$. Overall height, to top of sign, is $22 \frac{3}{4}''$.

SALES BOOSTER

The 24 standard stock items included in No. DP57 LOCK MER-CHANDISER were carefully selected after field tests to determine their qualities as "impulse purchase" items. Setting them out into full view of store traffic, in this eye catching compact form has proven highly profitable to dealers throughout the country by means of substantially increased sales volume.

Packed one per carton. Weight 48 lbs.

No. DP65 NIGHT LATCH ASSORTMENT AND FREE MERCHANDISING UNIT SOLVES THE INSTALLATION PROBLEM FOR "DO-IT-YOURSELFERS"

This unique ILCO night latch merchandiser has dramatically demonstrated the terrific power of the "Do-It-Yourself" sales approach by providing the answer to the well known installation bugaboo—how to bore the cylinder hole. Two boring tools are furnished with each merchandising unit. They are "loaned" as needed on a \$2.00 deposit.

Result; a frequent sales killer has been eliminated and a customer has been made happy by an "extra service".

No. DP65 includes five packaged and one mounted of each of the following popular night latches, Nos. D220, 263GY and 219C; two boring tools; one counter display as illustrated.

All items packed in a carton. Weight 33 lbs.

A SUPER-SALESMAN IN JUST FOUR SQUARE FEET OF FLOOR SPACE

No. 6000 Holds 21 fast moving Lockwood items for easy self-selection.

Attractively grained, full thickness hardwood panels rotate freely and accent the beauty of each piece.

Sturdy tubular frame with handsome bronze-tone finish.

Ample free literature for each item displayed.

Field tested and proven in major markets.

CONTAINS 21 FAST-MOVING LOCKWOOD ITEMS

Top Row — Left to Right

RT130x3x576For exterior doors	,
RT120x3For bedroom doors	
RT130xR5x574x3For exterior doors	
RT110x3For passage doors	i
RT120x3x26For bathroom doors	-
Chrome inside, brass outside.	1

Mount "A"

(Back)

Mount "B" SM2838x3......Classic Colonial design in a maximum security ex-

terior door lock
Mount "C"
DT130DLx3
DT130x26D
DT130DLxS5DL

x572x574x3

DT137DLx3 DT137x26D

Mount "E"

For exterior doors

Bottom Row—Left to Right

Mount	"D"
(Front)	
3006 (Lockwood screen and Storm door closers
3007 1	Storm door closers


D220.....Popular night latch 8597x3......Screen door latch knob

lever combination.

8970x3 Knocker. 5 Popular padlocks for fast turnover Nos. 320S, 324C, 373, 373A and 385.

SUBSTITUTION

This display stand is made to accommodate the specific mounts shown. Substitutions in design, finish, etc. of the products listed above can be made. For complete information contact our representative or write the factory direct.



SAMPLE MOUNTS

FOR "R", "S" AND "D" SERIES CYLINDRICAL LOCKSETS



Accommodates five sets — four at 2 3%" backset; one at 5" backset with trim plate, if desired.

No. M1016 Block Size 155%"x10"x134"

FOR "R", "S" AND "D" SERIES CYLINDRICAL LOCKSETS



Accommodates three sets usually passage, bath-bedroom and entry with 5" backset and trim plate, if desired.

No. M1013 Block Size 13" x 10" x 1 3/4"

FOR "R", "S" AND "D" SERIES CYLINDRICAL LOCKSETS



For displaying sets singly. Can accommodate No. 576 Trim Plate (on the square), if so desired.


No. M238 Block Size 6" x 43/4" x 13/4"

FOR "R", "S" AND "D" SERIES CYLINDRICAL LOCKSETS Cast Aluminum, Satin Finish



To demonstrate internal as well as external lock parts in operation.

No. M650 Block Size 3 %" x 4 3/4" x 1 3/4"



PORTABLE DISPLAY RACK

For use with No. M650 Mounts

Designed to hold three No. M650 mounts which slide in and out with ease. Made of hardwood and finished ebony black.

No. M657 Block Size 15½" x 5¼" x 2¾"

FOR REMODELOR SETS



Attractive display card in full color delivers the sales story at pointof-purchase. Produces impulse sales.

No. M633
Block Size
11½" x 4¾" x 1¾"
Card
7" x 9½" printed
both sides

FOR ENTRANCE HANDLE SETS


No. M635 Block Size 19" x 51/2" x 1 3/4"



FOR MORTISE KNOB

No. M631 Block Size 11½" x 4¾" x 1¾"

DORGUARD DEMONSTRATOR



No. M659

Made of solid birch in natural finish. Colorful, illustrated card attached explains DORGUARDS purpose and operation at a glance. Block Size

14" x 4" x 6" high

FOR ILCO NIGHT LATCHES



Any night latch listed in this catalog is available mounted on this mount. In ordering, merely suffix latch number with MTD, thus: 265-MTD.

Block Size 6" x 43/4" x 13/8"



WALL MOUNT

Four items included are Nos. 210, 218, 265, and 401 mounted on a block $17'' \times 4\sqrt[3]{4}'' \times 1\sqrt[3]{8}''$.

No. 85MT
Same as above with the following four Night Latches, Nos. 241B, 210B, 219C and 265.

No. 88MT



NIGHT LATCH MOUNT

Includes three Night Latches, Nos. 210B, 264GY and 218C.

No. 84MT Block Size 11½" x 4¾" x 1¾"

SAMPLE MOUNTS

FOR PUSH-PULL SCREEN DOOR SETS



Solid hardwood mount, natural finish.

No. M655 Block Size 45/8" x 41/8" x 11/8"

FOR SCREEN DOOR SETS



Individual mount for all screen door sets.

No. M651 Block Size 31/4" x 51/2" x 11/8"

FOR SCREEN-STORM DOOR SETS



Offers customer choice of four popular sets.

No. M658 Block Size 10½" x 7¼" x 1½"

SCREEN-STORM DOOR CLOSER DEMONSTRATOR



No. M626 For 3006 Closer Size 63/4" x 21" x 4"

DOOR CLOSER DEMONSTRATOR

No. M621 Size 7" x 16" x 171/2" For Nos. B30 or 22 Closers

No. M622 7" x 24" x 11 ½" For Nos. B830 or B1130 Closers (Parallel arm).

FOR PANIC EXIT DEVICES (Made of Aluminum)



No. M645
Block Size
30" x 4" x 1 34".
For vertical rod devices.

No. M646

Block Size
21" x 4" x 1 3/4".

For rim device with handle.

No. M647

Block Size

16" x 4" x 1 3/4".


For rim devices without handle.

PADLOCK ASSORTMENT



No. 59PA

Assortment consists of nine popular padlock numbers in the following quantities; Six No. 324; Six No. 320G; Six No. 320GA; Six No. 373; Three No. 391; Two No. 385; Two No. 384; Two No. 373A; Two No. 382. Colorful Blue, Red and Yellow display quickly attracts attention and means extra sales. (See Pages 22 to 24 for description of padlocks.)



MARINE PADLOCK ASSORTMENT

Including FREE Display Board


No. 60MPA

The boating market is booming and these padlocks offer you a chance to get a share of it. This handsome counter or wall display board is one sure-fire and easy way for you to cash in on America's No. 1 leisure pastime. Assortment consists of 3 each of the following six numbers — 384B, 373B, 382B, 373NB, 373½WB, 373WB. (See pages 22-24 for description of padlocks.)

PADLOCK MERCHANDISER

FINISHED
IN THREE
ATTRACTIVE
COLORS

FREE display board with each assortment



No. 21PA

You'll want more than one of these ILCO Padlock Merchandisers to hang on your walls or stand on your counters and in your windows. Assortment includes one each of the following numbers; 391, 384, 385, 373, 317, 320GA, 390, 320G, 324, 309A, 317A, 383. Every lock a quick seller and top profit maker. (See Pages 22-24 for description of padlocks.)

ILCO KEY BLANKS

